Note: This datasheet may be out of date

Please download the latest datasheet of NFA21SL337V1A48# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NFA21SL337V1A48%23

"#" indicates a package specification code.

### NFA21SL337V1A48#








< List of part numbers with package codes > NFA21SL337V1A48B NFA21SL337V1A48L



### Appearance & Shape









### **Features**

- 1. Steep insertion loss characteristics
- 2. Suitable for noise suppression in 800MHz or higher frequency
- 3. Size: 2.0x1.25mm
- 4. 4 circuits in one package

Applications

Noise suppression for LCD line



### **Applications**

Other Usage For general



### Packaging Information

Packaging	Specifications	Standard Packing Quantity
В	Bulk(Bag)	1000
L	180mm Embossed Tape	4000

1 of 3

### Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



NFA21SL337V1A48#

Note: This datasheet may be out of date.

Manufacturing Co., Ltd.

Please download the latest datasheet of NFA21SL337V1A48# from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=NFA21SL337V1A48%23

"#" indicates a package specification code.



## **Specifications**

Shape	SMD
Size Code (in inch)	0805
Length	2.0mm
Length Tolerance	±0.1mm
Width	1.25mm
Width Tolerance	±0.1mm
Thickness	0.85mm
Thickness Tolerance	±0.1mm
Operating Temperature Range	-55°C to 125°C
Mass(typ.)	0.012g
Number of Circuit	4
Rated Current	100mA
Rated Voltage	10Vdc
Withstanding Voltage	30Vdc
Insulation Resistance(min.)	1000ΜΩ
Insertion Loss	6dB max.(at Cut-off Frequency),20dB min.(at 800MHz),20dB min.(at 900MHz)
Nominal Cut-off Frequency	330MHz
Size Code (in mm)	2012

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




# NFA21SL337V1A48#


Note: This datasheet may be out of date.


Please download the latest datasheet of NFA21SL337V1A48# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NFA21SL337V1A48%23

"#" indicates a package specification code.








**Insertion Loss Characteristics** 

Insertion Loss Characteristics (Main Items)



**Equivalent Circuit** 

3 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

