

NFA21SL506X1A48#


In Production RoHS REACH

< List of part numbers with package codes > NFA21SL506X1A48B NFA21SL506X1A48L



Appearance & Shape





Note: This datasheet may be out of date. Please download the latest datasheet of NFA21SL506X1A48# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NFA21SL506X1A48%23

"#" indicates a package specification code.

1. Steep insertion loss characteristics

Features

- 2. Suitable for noise suppression in 800MHz or higher frequency
- 3. Size: 2.0x1.25mm
- 4.4 circuits in one package

Applications Noise suppression for LCD line

Applications

Other Usage

For general

Packaging Information

| Packaging | Specifications | Standard |
|-----------|---------------------|----------|
| | | Packing |
| | | Quantity |
| В | Bulk(Bag) | 1000 |
| L | 180mm Embossed Tape | 4000 |

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Rata Product Search Data Sheet

NFA21SL506X1A48#

Note: This datasheet may be out of date. Please download the latest datasheet of NFA21SL506X1A48# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NFA21SL506X1A48%23

"#" indicates a package specification code.



Specifications

| Shape | SMD | |
|--------------------------------|--|--|
| Size Code (in inch) | 0805 | |
| Length | 2.0mm | |
| Length Tolerance | ±0.1mm | |
| Width | 1.25mm | |
| Width Tolerance | ±0.1mm | |
| Thickness | 0.85mm | |
| Thickness Tolerance | ±0.1mm | |
| Operating Temperature Range | -55°C to 125°C | |
| Mass(typ.) | 0.012g | |
| Number of Circuit | 4 | |
| Rated Current | 20mA | |
| Rated Voltage | 10Vdc | |
| Withstanding Voltage | 30Vdc | |
| Insulation Resistance(min.) | 1000ΜΩ | |
| Insertion Loss | 0dB to 6dB(at Cut-off Frequency),30dB min.(at 500MHz),20dB min.(at 1000MHz) | |
| Nominal Cut-off Frequency | 50MHz | |
| Size Code (in mm) | 2012 | |

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Product Search Data Sheet

NFA21SL506X1A48#


Note: This datasheet may be out of date. Please download the latest datasheet of NFA21SL506X1A48# from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en/products/productdetail?partno=NFA21SL506X1A48%23

"#" indicates a package specification code.




Product Data





Insertion Loss Characteristics

Insertion Loss Characteristics (Main Items)



Equivalent Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

