

Product Search Data Sheet

DXW21HN5011B#


In Production RoHS REACH

< List of part numbers with package codes > DXW21HN5011BB DXW21HN5011BL



Appearance & Shape







1. Ultra Miniature Wire Wound Transformer (2.0×1.2×0.9mm)

- 2. Low Insertion Loss
- 3. Wideband Frequency Range
- 4. Surface Mount

Applications

TV tuners, Cable TV tuners and Communication application that require unbalance mode to balance mode conversion.

Applications

Other Usage

For general

Packaging Information

Packaging	Specifications	Standard
		Packing
		Quantity
В	Bulk(Bag)	500
L	180mm Embossed Tape	3000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Note: This datasheet may be out of date. Please download the latest datasheet of DXW21HN5011B# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=DXW21HN5011B%23

"#" indicates a package specification code.



DXW21HN5011B#

Note: This datasheet may be out of date. Please download the latest datasheet of DXW21HN5011B# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=DXW21HN5011B%23

"#" indicates a package specification code.



Specifications

Operating Temperature Range	-40°C to 85°C	
Frequency Range	100MHz to 1000MHz	
Insertion Loss	1.0dB max.(at Freq. Range)	
Size Code (in mm)	2012	
Size Code (in inch)	0805	
Length	2mm	
Length Tolerance	±0.2mm	
Width	1.2mm	
Width Tolerance	±0.2mm	
Thickness	0.9mm	
Thickness Tolerance	±0.1mm	
Rated Voltage	20Vdc	
Withstanding Voltage	50Vdc	
Port Impedance	50Ω - 50Ω	
CMRR(min.)	10dB	
DC Resistance(max.)	0.35Ω	
Insulation Resistance(min.)	10ΜΩ	
Mass(typ.)	0.009g	

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.






Product Search Data Sheet


DXW21HN5011B#


Note: This datasheet may be out of date. Please download the latest datasheet of DXW21HN5011B# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=DXW21HN5011B%23

"#" indicates a package specification code.








Insertion Loss Characteristics





Equivalent Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

