

# LQG15WZ7N5H02#

Note: This datasheet may be out of date.

Please download the latest datasheet of LQG15WZ7N5H02# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=LQG15WZ7N5H02%23

"#" indicates a package specification code.

Size Code 1005 (0402) in mm (in inch), Multilayer Type, High Q, Automotive available (Infotainment)



















< List of part numbers with package codes >

LQG15WZ7N5H02B


LQG15WZ7N5H02D

LQG15WZ7N5H02J



## Appearance & Shape







### References

| Packaging | Specifications   | Standard<br>Packing<br>Quantity |
|-----------|------------------|---------------------------------|
| В         | Bulk(Bag)        | 100                             |
| D         | 180mm Paper Tape | 10000                           |
| J         | 330mm Paper Tape | 40000                           |

| Mass (typ.) |       |        |  |
|-------------|-------|--------|--|
| 1 p         | viece | 0.001g |  |

1 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





# LQG15WZ7N5H02#

Note: This datasheet may be out of date.

Please download the latest datasheet of LQG15WZ7N5H02# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=LQG15WZ7N5H02%23

"#" indicates a package specification code.



# **Specifications**

| L size   | 1.0±0.05mm     |
|--|----------------|
| W size   | 0.6±0.05mm     |
| T size   | 0.5±0.1mm      |
| Size code inch (mm)  | 0402 (1005)    |
| Inductance   | 7.5nH±3%       |
| Inductance Test Frequency  | 100MHz         |
| Rated current (Itemp) (Based on Temperature rise)                  | 600mA          |
| Max. of DC resistance  | 0.16Ω          |
| Q(min.)  | 23             |
| Q Test Frequency   | 250MHz         |
| Self resonance frequency (min.)                                    | 4000MHz        |
| Operating Temperature Range(Self-temperature rise is not included) | -55°C to 125°C |
| Brand  | Murata         |
| Series   | LQG15WZ_02     |

2 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



### Product Search Data Sheet

Please download the latest datasheet of LQG15WZ7N5H02# from the official website of Murata Manufacturing Co., Ltd.

Note: This datasheet may be out of date.

http://www.murata.com/en/products/productdetail?partno=LQG15WZ7N5H02%23


"#" indicates a package specification code.


# LQG15WZ7N5H02#




### Characteristic Data

The charts below may show another part number which shares its characteristics.







3 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

