

MDH6045C-151MA#

Note: This datasheet may be out of date.

Please download the latest datasheet of MDH6045C-151MA# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=MDH6045C-151MA%23

"#" indicates a package specification code.

Comply with ISO16750-3 (vibration test for Engine)


















< List of part numbers with package codes > MDH6045C-151MA=P3



Appearance & Shape







References

| Packaging | Specifications | Standard Packing Quantity |
|-----------|------------------|---------------------------------|
| =P3 | 330Embossed Tape | 1000 |

| Mass (typ.) | |
|-------------|-------|
| 1 piece | 0.55g |



Notices

The saturation allowable DC current value is specified when the decrease of the nominal inductance value at 30%. Rated current (based on temperature rise) is specified when temperature of the inductor on our PCB for test purpose is raised 40°C by DC current.

1 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





MDH6045C-151MA#

Note: This datasheet may be out of date.

Please download the latest datasheet of MDH6045C-151MA# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=MDH6045C-151MA%23

"#" indicates a package specification code.



Specifications

| L size | 6.3±0.2mm |
|---|----------------|
| W size | 6.0±0.2mm |
| T size | 4.5±0.3mm |
| Size code inch (mm) | 2524 (6360) |
| Inductance | 150µH±20% |
| Inductance Test Frequency | 0.1MHz |
| Rated current (Isat) (Based on Inductance change) | 520mA |
| Rated current (Itemp) (Based on Temperature rise) | 540mA |
| Max. of DC resistance | 0.676Ω |
| Operating Temperature Range (Self-temperature rise is included) | -55°C to 150°C |
| Class of magnetic shield | Ferrite Core |
| Brand | Murata |
| DC Resistance Intermediate Values | 0.520Ω±30% |
| Series | MDH6045C |

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





MDH6045C-151MA#

Note: This datasheet may be out of date.

Please download the latest datasheet of MDH6045C-151MA# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=MDH6045C-151MA%23


"#" indicates a package specification code.



Notice For General

Max. current (DC, AC) as function of product temperature (derating curve).

Derating of Rated Current



3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

