


Product Search Data Sheet

DSS1NB31H473Q91#

In Production RoHS REACH

< List of part numbers with package codes > DSS1NB31H473Q91A

Appearance & Shape





http://www.murata.com/en/products/productdetail?partno=DSS1NB31H473Q91%23

"#" indicates a package specification code.

Features

DSS1 series is a compact, high performance lead type 3 terminal capacitor which can be mounted in 2.54mm pitch. Its three terminal structure enables nice high frequency performance. Wide capacitance variation enables flexible selection for various noise frequencies. High speed mounting is available with automatic insertion machine.

Applications

Other Usage

For general

Packaging Information

| Packaging | Specifications | Standard Packing Quantity |
|-----------|----------------|---------------------------------|
| A | Ammo Pack | 1500 |

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





DSS1NB31H473Q91#

Note: This datasheet may be out of date. Please download the latest datasheet of DSS1NB31H473Q91# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=DSS1NB31H473Q91%23

"#" indicates a package specification code.



Specifications

| Shape | Lead | |
|--------------------------------|---------------------------------------|--|
| Length | 8.5mm | |
| Length Tolerance | max. | |
| Width | 3.5mm | |
| Width Tolerance | max. | |
| Thickness | 7.5mm | |
| Thickness Tolerance | max. | |
| Rated Current | 6A | |
| Operating Temperature Range | -40°C to 85°C | |
| Mass(typ.) | 0.45g | |
| Number of Circuit | 1 | |
| Insulation Resistance(min.) | 1000ΜΩ | |
| Rated Voltage | 50Vdc | |
| Withstanding Voltage | 125Vdc | |
| Capacitance | 47000pF | |
| Capacitance Tolerance | ±10% | |
| Structure/Shape | Small type beads inside (straight) | |

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.






DSS1NB31H473Q91#


Note: This datasheet may be out of date. Please download the latest datasheet of DSS1NB31H473Q91# from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en/products/productdetail?partno=DSS1NB31H473Q91%23

"#" indicates a package specification code.




INNOVATOR IN ELECTRONICS





Insertion Loss Characteristics

Insertion Loss Characteristics (Main Items)



Equivalent Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

