

Product Search Data Sheet

Please download the latest datasheet of GRM21B7U1H433JA01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=GRM21B7U1H433JA01%23

Note: This datasheet may be out of date.

"#" indicates a package specification code.

## GRM21B7U1H433JA01#














< List of part numbers with package codes > GRM21B7U1H433JA01L GRM21B7U1H433JA01K



### Appearance & Shape







### References

Packaging	Specifications	Standard
		Packing
		Quantity
L	180Embossed Tape	3000
K	330Embossed Tape	10000

Mass (typ.)		
1 piece	16.0mg	
φ180mm Reel	91g	

1 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



# GRM21B7U1H433JA01#

Note: This datasheet may be out of date.

Please download the latest datasheet of GRM21B7U1H433JA01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=GRM21B7U1H433JA01%23

"#" indicates a package specification code.



# **Specifications**

Length	2.0±0.1mm
Width	1.25±0.1mm
Thickness	1.25±0.1mm
Capacitance	43000pF ±5%
Distance between external terminals g	0.7mm min.
External terminal size e	0.2 to 0.7mm
Operating Temperature Range	-55°C to 125°C
Rated Voltage	50Vdc
Size code in inch(mm)	0805 (2012M)
TC	-750±120ppm/°C
Temperature characteristics (complied standard)	U2J(EIA)
Temperature range of temperature characteristics	25°C to 85°C

2 of 2

### Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

