

DXW21BZ7511T#

Note: This datasheet may be out of date.

Please download the latest datasheet of DXW21BZ7511T# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=DXW21BZ7511T%23

"#" indicates a package specification code.









< List of part numbers with package codes >

DXW21BZ7511TB


DXW21BZ7511TK


DXW21BZ7511TL



Appearance & Shape







Applications

Automotive Usage

Infotainment



Packaging Information

Packaging	Specifications	Standard Packing Quantity
В	Bulk(Bag)	500
K	330mm Embossed Tape	10000
L	180mm Embossed Tape	2000



Features

- 1. Ultra miniature size and wire wound type microchip transformer. 2.0x1.2x1.2mm (EIAcode:0805)
- 2. Using for GHz frequency range (1 to 1.5GHz) about BS or CS broadcast.
- 3. Surface mount type. Lead Free.

1 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





DXW21BZ7511T#

Note: This datasheet may be out of date.

Please download the latest datasheet of DXW21BZ7511T# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=DXW21BZ7511T%23

"#" indicates a package specification code.



Specifications

Operating Temperature Range	-40°C to 105°C	
Frequency Range	50MHz to 870MHz	
Insertion Loss	1.0dB max.(at Freq. Range)	
Size Code (in mm)	2012	
Size Code (in inch)	0805	
Length	2mm	
Length Tolerance	±0.2mm	
Width	1.2mm	
Width Tolerance	±0.2mm	
Thickness	1.2mm	
Thickness Tolerance	±0.2mm	
Power Rating	27dBm	
Rated Voltage	20Vdc	
Withstanding Voltage	50Vdc	
Port Impedance	75Ω - 75Ω	
CMRR(min.)	20dB	
DC Resistance(max.)	0.77Ω	
Insulation Resistance(min.)	10ΜΩ	
Mass(typ.)	0.011g	

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



DXW21BZ7511T#


Note: This datasheet may be out of date.


Please download the latest datasheet of DXW21BZ7511T# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=DXW21BZ7511T%23

"#" indicates a package specification code.








Insertion Loss Characteristics

CMRR Characteristics



Equivalent Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.