

Note: This datasheet may be out of date. Please download the latest datasheet of LQH32NH2R7J23# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=LQH32NH2R7J23%23

"#" indicates a package specification code.

It can be used in 125 °C environment.


LQH32NH2R7J23#



< List of part numbers with package codes > LQH32NH2R7J23K LQH32NH2R7J23L









References

| Packaging | Specifications | Standard Packing Quantity |
|-----------|------------------|---------------------------------|
| К | 330Embossed Tape | 7500 |
| L | 180Embossed Tape | 2000 |

| Mass (typ.) | | |
|-------------|-------|--|
| 1 piece | 0.06g | |



Notices

When rated current is applied to the products, selftemperature rise shall be limited to 20°C max and inductance will be within ±10% of initial inductance value.

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

- without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





LQH32NH2R7J23#

Note: This datasheet may be out of date. Please download the latest datasheet of LQH32NH2R7J23# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=LQH32NH2R7J23%23

"#" indicates a package specification code.



Specifications

| L size | 3.2±0.3mm |
|--|----------------|
| W size | 2.5±0.2mm |
| T size | 2.0±0.2mm |
| Size code inch (mm) | 1210 (3225) |
| Inductance | 2.7µH±5% |
| Inductance Test Frequency | 1MHz |
| Rated current (Itemp) (Based on Temperature rise) | 495mA |
| Max. of DC resistance | 0.18Ω |
| Class of magnetic shield | No Shield |
| Q(min.) | 25 |
| Q Test Frequency | 1MHz |
| Self resonance frequency (min.) | 70MHz |
| Brand | Murata |
| DC Resistance Intermediate Values | 0.15Ω±20% |
| Operating Temperature Range | -40°C to 125°C |
| Series | LQH32NH_23 |

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Note: This datasheet may be out of date. Please download the latest datasheet of LQH32NH2R7J23# from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en-gb/products/productdetail?partno=LQH32NH2R7J23%23


"#" indicates a package specification code.


LQH32NH2R7J23#

Characteristic Data

The charts below may show another part number which shares its characteristics.







3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

- without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

