

Note: This datasheet may be out of date. Please download the latest datasheet of LQH5BPB220MT0# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=LQH5BPB220MT0%23

"#" indicates a package specification code.

105°C Operation Available




< List of part numbers with package codes > LQH5BPB220MT0K LQH5BPB220MT0L



LQH5BPB220MT0#





(in mm)



References

Packaging	Specifications	Standard
		Packing
		Quantity
К	330Embossed Tape	3000
L	180Embossed Tape	500

Mass (typ.)		
1 piece	0.22g	



Notices

When rated current is applied to the products, inductance will be within ±30% of nominal inductance value. When rated current is applied to the products, the temperature rise caused by selfgenerated heat shall be limited to 40°C max. Keep the temperature (ambient temperature plus selfgeneration of heat) under 125°C.

1 of 4

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

- without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications





LQH5BPB220MT0#

Note: This datasheet may be out of date. Please download the latest datasheet of LQH5BPB220MT0# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=LQH5BPB220MT0%23

"#" indicates a package specification code.



Specifications

L size	5.0±0.2mm
W size	5.0±0.2mm
T size	2.0±0.2mm
Size code inch (mm)	2020 (5050)
Inductance	22µH±20%
Inductance Test Frequency	100kHz
Rated current (Isat) (Based on Inductance change)	1.4A
Rated current (Itemp)	1.05A(Ambient temp.85°C)0.
(Based on Temperature rise)	55A(Ambient temp.105°C)
Max. of DC resistance	0.3108Ω
Operating Temperature Range (Self-temperature rise is included)	-40℃ to 125℃
Class of magnetic shield	Magnetic Resin
Self resonance frequency (min.)	15MHz
Operating Temperature Range(Self-temperature rise is not included)	-40℃ to 105℃
Brand	Murata
DC Resistance Intermediate Values	0.259Ω±20%
Series	LQH5BPB_T0

2 of 4

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.





Note: This datasheet may be out of date. Please download the latest datasheet of LQH5BPB220MT0# from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en-gb/products/productdetail?partno=LQH5BPB220MT0%23


"#" indicates a package specification code.


LQH5BPB220MT0#


Characteristic Data

The charts below may show another part number which shares its characteristics.









Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.






Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of LQH5BPB220MT0# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=LQH5BPB220MT0%23

"#" indicates a package specification code.



LQH5BPB220MT0#

4 of 4

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.



^{2.} This datasheet has only typical specifications because there is no space for detailed specifications.