

Note: This datasheet may be out of date. $Please\ download\ the\ latest\ data sheet\ of\ GRM31XB11A335KAA7\#\ from\ the\ official\ website\ of\ Muratangle and the statest and the stat$

Manufacturing Co., Ltd.

"#" indicates a package specification code.

http://www.murata.com/en/products/productdetail?partno=GRM31XB11A335KAA7%23

GRM31XB11A335KAA7#















< List of part numbers with package codes > GRM31XB11A335KAA7L GRM31XB11A335KAA7K



Appearance & Shape







References

		Standard
Packaging	Specifications	Packing
		Quantity
L	180Embossed Tape	3000
K	330Embossed Tape	10000

Mass (typ.)		
1 piece	34.0mg	
φ180mm Reel	149g	

1 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



GRM31XB11A335KAA7#

Note: This datasheet may be out of date.

Please download the latest datasheet of GRM31XB11A335KAA7# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=GRM31XB11A335KAA7%23

"#" indicates a package specification code.



Specifications

Length	3.2±0.2mm	
Width	1.6±0.2mm	
Thickness	1.2±0.1mm	
Capacitance	3.3µF ±10%	
Distance between external terminals g	1.5mm min.	
External terminal size e	0.3 to 0.8mm	
Operating Temperature Range	-25°C to 85°C	
Rated Voltage	10Vdc	
Size code in inch(mm)	1206 (3216M)	
Capacitance change rate	±10.0%	
Temperature characteristics	B(JIS)	
(complied standard)		
Temperature range of	-25°C to 85°C	
temperature characteristics		

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

