

Product Search Data Sheet

Note: This datasheet may be out of date.

Please download the latest datasheet of WMRAG32K76CS2C00R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=WMRAG32K76CS2C00R0

# WMRAG32K76CS2C00R0










## Appearance & Shape







### **Features**

MEMS technology was used to realize the world's smallest size resonator with very low ESR characteristics that is currently unachievable by quartz crystal resonators.

### Features

- 1. The MEMS resonator is extremerly small size (0906), and contribute to reduction in mounting area.
- 2. The MEMS resonator with low ESR is realized lower power consumption by optimizing IC gain.
- 3. It is available for reflow soldering, wire bonding and transfer molding.



## **Applications**

Other Usage	Consumer
-------------	----------



## Packaging Information

Packaging	Specifications	Standard
		Packing
		Quantity
R0	180mm Plastic Tape	5000
R1	180mm Plastic Tape	1000

1 of 2

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



### Product Search Data Sheet

Note: This datasheet may be out of date.  $Please\ download\ the\ latest\ data sheet\ of\ WMRAG32K76CS2C00R0\ from\ the\ official\ website\ of\ Murata$ Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=WMRAG32K76CS2C00R0

# WMRAG32K76CS2C00R0



# **Specifications**

Product Type	MEMS Resonator	
Series	WMRAG	
Frequency	32.7680kHz	
Frequency Tolerance	+/-20ppm max. (+25+/-1°C)	
Operating Temperature Range	-40°C~85°C	
Frequency Shift by Temperature	-200 to +10ppm max.	
Frequency Aging	+/-3ppm max./year	
Equivalent Series Resistance (ESR)	75kohm max.	
Drive Level (DL)	0.2μW max.	
Load Capacitance (Cs)	8pF	
Built-in Load Capacitance (CL1/CL2)	6.9pF	
Shape	SMD	
Wash	Not available (Please be sure to consult with our sales representative or engineer whenever and prior to using the products.)	
L x W (size)	0.9x0.6mm	
Mass	0.4mg	

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

