

Timing Device > CERALOCK (MHz) > Series












How to check EU RoHS Compliance of Our Products is [here](#).

<a href="#">Product Lifecycle Stage</a>	in Production
<a href="#">Recommended Rank</a>	Preferred

**Specifications**

**Details**

Global Part Number	CSTCC_G_A
Previous Part Number	CSTCC_MGA
Oscillating Frequency	2.00 to 3.99MHz
Initial Tolerance	±0.5%
Frequency Shift by Temperature	±0.4% [-0.6% to +0.3%:Built-in Capacitance 47pF type within Freq.2.00 to 3.49MHz]
Operating Temperature Range	-40 to 125..
Wash	Available
Ultrasonic Wash	Available
Capacitor	Built in
Frequency Tolerance	Available in ±0.3%,±0.2%
Use	
Applications	For automotive electronics

-  [Part Numbering](#)
-  [Appearance/Dimensions\\_\(3.00MHz-\)](#)
-  [Features\\_Applications](#)
-  [Frequency\\_Temperature\\_Characteristics](#)
-  [Standard\\_Land\\_Patterns](#)
-  [Notice](#)
-  [Packaging2\\_\(3.00MHz-\)](#)
-  [Minimum\\_Quantity\\_\(Supplementation\)](#)
-  [Appearance\\_\(2.00\\_to\\_2.99MHz\)](#)
-  [Dimensions\\_\(2.00\\_to\\_2.99MHz\)](#)
-  [Packaging\\_\(2.00\\_to\\_2.99MHz\)](#)

**Minimum Quantity**

180mm Paper Tape	
180mm Embossed Tape	2000
330mm Paper Tape	
330mm Embossed Tape	6000
Bulk Case	
Bulk(Bag)	500
Ammo Pack	
320Reel	
Magazine	
Box	

**Please approve our product specifications or to transact the approval sheet for product specifications before ordering.**  
**Please read rating and !Cautions first.**  
**Product specifications in this catalog are as of March 2015**  
**Please make sure to read the Murata's [Product Policy](#) ,too.**

All products and company names herein are trademarks or registered trademarks of their respective owners.

UP ^