

Note: This datasheet may be out of date. Please download the latest datasheet of CSBLA800KJ58-B0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=CSBLA800KJ58-B0

# CSBLA800KJ58-B0










## Appearance & Shape







### **Applications**

Other Usage Consumer/Industrial	
---------------------------------	--



## **Packaging Information**

Packaging	Specifications	Standard Packing Quantity
В0	Bulk	1000



### **Features**

The CSBLAseries ceramic resonators owe their development to MURATA's innovative expert technologies and the application of mass production techniques typically utilized in the manufacture of piezoelectric ceramic components. Because of their high mechanical Q and consistent high quality, the CSBLAseries are ideally suited to microprocessor and remote control unit applications.

### Features

- 1. Stable over a wide temperature range and with respect to longterm aging.
- 2. Fixed, tuned, solid-state devices
- 3. Miniature and lightweight
- 4. Exhibit excellent shock resistance performance.
- 5. Oscillating circuits requiring no adjustment can be designed by utilizing these resonators in conjunction with transistors or appropriate ICs.

1 of 2

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





# CSBLA800KJ58-B0

Note: This datasheet may be out of date.

Please download the latest datasheet of CSBLA800KJ58-B0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=CSBLA800KJ58-B0



# **Specifications**

	Ceramic Resonator
Product Type	
	(CERALOCK)
Series	CSBLA J (430kHz-)
	_ ` '
Frequency	800.0kHz
Frequency Tolerance	+/-0.50% max.
Operating Temperature	
	-20°C~80°C
Range	
Frequency Shift by	+/-0.30% max.
Temperature	
Frequency Aging	+/-0.30% max.
Troquonoy riging	7 0.00 % Hidx.
Resonant Impedance (R1)	60ohm max.
Shape	Lead
Wash	available
L x W (size)	6.0x5.0mm
Mass	108mg

2 of 2

### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

