

Resonators > CERALOCK (kHz) > Series

How to check EU RoHS Compliant of Our Products is [here](#).

Product Lifecycle Stage	in Production
Recommended Rank	Preferred














Specification

Global Part Number	CSBLA_E
Previous Part Number	CSB_E(CSB_P)
Oscillating Frequency	375 to 699kHz
Initial Tolerance	
Temp. Stability	±0.3%
Temperature Range	-20 to +80°C
Wash	Not Available
Ultrasonic Wash	Not Available
Capacitor	External
Frequency Tolerance	±2kHz,±1kHz
Use	
Airtightness	

Minimum Quantity

180mm Paper Tape	
180mm Embossed Tape	
330mm Paper Tape	
330mm Embossed Tape	
Bulk Case	
Bulk(Bag)	500
Ammo Pack	
320Reel	
Magazine	50
Box	

Details

- ?  [Part Numbering](#)
- ?  [Appearance_1\(375_to_429kHz\)](#)
- ?  [Dimensions_1\(375_to_429kHz\)](#)
- ?  [Appearance/Dimensions_\(430_to_509kHz\)](#)
- ?  [Appearance/Dimensions_\(510_to_699kHz\)](#)
- ?  [Features and Applications](#)
- ?  [Temperature Characteristics](#)
- ?  [Basic Oscillation Circuit](#)
- ?  [Notice \(storage and operating condition\)](#)
- ?  [Notice \(rating\)](#)
- ?  [Notice \(soldering and mounting\)](#)
- ?  [Notice \(handling\)](#)
- ?  [Minimum Quantity\[Supplementation\]](#)

Please approve our product specifications or to transact the approval sheet for product specifications before ordering. Please read rating and !Cautions first.
Product specifications in this catalog are as of January 2008.

All products and company names herein are trademarks or registered trademarks of their respective owners.