

Note: This datasheet may be out of date. Please download the latest datasheet of CSTNR7M37GH5L000R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=CSTNR7M37GH5L000R0

CSTNR7M37GH5L000R0












Appearance & Shape







Features

MURATA's frequency adjustment and packaging technology expertise has enabled the development of the chip CERALOCK(R) with built-in load capacitors.

Features

- 1. Oscillation circuits do not require external load capacitors.
- 2. Available for a wide frequency range.
- 3. Extremely small and have a low profile.
- 4. No adjustment is necessary for oscillation circuits.
- 5. Stable supply is ensured due to not using precious metal(Palladium).



Applications

Other Usage Consumer/Industrial



Packaging Information

Packaging	Specifications	Standard Packing Quantity
R0	180mm Embossed Tape	3000

1 of 2

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Product Search Data Sheet

Note: This datasheet may be out of date. $Please\ download\ the\ latest\ data sheet\ of\ CSTNR7M37GH5L000R0\ from\ the\ official\ website\ of\ Murata$ Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=CSTNR7M37GH5L000R0

CSTNR7M37GH5L000R0



Specifications

	Ceramic Resonator	
Product Type	(CERALOCK)	
Series	CSTNR_GH5L	
Frequency	7.370MHz	
Frequency Tolerance	+/-0.07% max.	
Operating Temperature Range	-20°C~85°C	
Frequency Shift by Temperature	+/-0.11% max.	
Frequency Aging	+/-0.07% max.	
Resonant Impedance (R1)	50ohm max.	
Built-in Load Capacitance (CL1/CL2)	39pF	
Shape	SMD	
Wash	Not available	
L x W (size)	4.5x2.0mm	
Mass	26.47mg	

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

