



2.0×1.6mm for Consumer Products/ Mobile Communication/ Automotive



AEC-Q200 RoHS Compliant

Features

- Support a wide range of applications
- Ultra-miniature and low profile (2.05×1.65×0.45mm)
- Ceramic package
- Reflow compatible

Applications

- ECU
- Automotive Camera
- Digital Electronics
- Mobile Communication

How to Order

CX2016SA 20000 D0 G S S CC
① ② ③ ④ ⑤ ⑥ ⑦

① Series	② Frequency
③ Load Capacitance	④ Frequency Tolerance
D0 8 pF	G ±15×10 ⁻⁶
⑤ Operating Temp. Range	⑥ Frequency Temp. Stability
SS -40 to +125°C	±50×10 ⁻⁶
TW -40 to +150°C	±200×10 ⁻⁶

⑦ Individual Specification
(STD Specification is "CC".)

Packaging (Tape & Reel 3000/ 15000 pcs./ reel)

Specifications

Item	Symbol	Specification	Unit	Remarks
Frequency Range	f _{nom}	16, 20, 24, 25, 26, 27, 30, 32, 37.4, 38.4, 40, 48, 50	MHz	Please contact us for other frequency range.
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	8	pF	Please contact us for other CL requirements.
Frequency Tolerance	f _{tol}	±15	×10 ⁻⁶	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	10μW(200μW max.)	μW	
Operating Temp. Range	T _{use}	-40 to +125 -40 to +150	°C	
Storage Temp. Range	T _{stg}	-40 to +150	°C	
Frequency Temp. Characteristics	f _{tem}	±50 ±200	×10 ⁻⁶	Freq. deviation from the value at 25°C


Please contact us for other specifications.

Table 1 Motional Series Resistance Please contact us for other frequency range.

Frequency Range	Motional Series Resistance
16MHz	200 Ω max.
20MHz	150 Ω max.
32MHz	60 Ω max.
50MHz	50 Ω max.


Dimensions

(Unit: mm)



Recommended Land Pattern

(Unit: mm)



As of August 2021

