

Timing Device > CERALOCK (MHz) > Part Number










How to check EU RoHS Compliance of Our Products is [here](#).

Product Lifecycle Stage	in Production
Recommended Rank	Preferred

Specifications

Details

Global Part Number	CSTCC10M0G53-R0
Previous Part Number	CSTCC2.00MG-TC
Nominal Frequency	2.000MHz
Initial Tolerance	±0.5%
Resonant Frequency	80ohm
Frequency Shift by Temperature	±0.3%
Operating Temperature Range	-20 to +80...
Frequency Aging	±0.3%
Wash	Not Available
Ultrasonic Wash	Not Available
Built-in Load Capacitance	15pF
Use	For consumer electronics

-  [Part Numbering](#)
-  [Appearance](#)
-  [Dimensions](#)
-  [Features and Applications](#)
-  [Frequency Temperature Characteristics](#)
-  [Standard Land Pattern](#)
-  [Notice](#)
-  [Packaging](#)
-  [Minimum Quantity](#)

Minimum Quantity

180mm Paper Tape	
180mm Embossed Tape	2000
330mm Paper Tape	
330mm Embossed Tape	
Bulk Case	
Bulk(Bag)	
Ammo Pack	
320Reel	
Magazine	
Box	

Please approve our product specifications or to transact the approval sheet for product specifications before ordering.
Please read rating and !Cautions first.
Product specifications in this catalog are as of March 2015
Please make sure to read the Murata's [Product Policy](#) ,too.

All products and company names herein are trademarks or registered trademarks of their respective owners.

UP ^