

Resonators > CERALOCK (MHz) > Series














How to check EU RoHS Compliant of Our Products is [here](#).

| | |
|---|---------------|
| Product Lifecycle Stage | in Production |
| Recommended Rank | Preferred |

Specification

| | |
|-----------------------|--|
| Global Part Number | CSTCR_G |
| Previous Part Number | |
| Oscillating Frequency | 4.00 to 7.99MHz |
| Initial Tolerance | ±0.5% |
| Temp. Stability | ±0.2% |
| Temperature Range | -20 to 80°C |
| Wash | Not Available |
| Ultrasonic Wash | Not Available |
| Capacitor | Built in |
| Frequency Tolerance | Tight tolerance frequency(Intra ±0.1%) |
| Use | The size of external electrode is not same as CSTCR_G15C and CSTCR_G15L. |
| Applications | For consumer electronics |

Details

- ?  [Part Numbering](#)
- ?  [Appearance](#)
- ?  [Dimensions](#)
- ?  [Features, Applications](#)
- ?  [Temperature Characteristics](#)
- ?  [Basic Oscillation Circuit](#)
- ?  [Standard Land Pattern Dimensions](#)
- ?  [Notice \(storage and operating condition\)](#)
- ?  [Notice \(rating\)](#)
- ?  [Notice \(soldering and mounting\)](#)
- ?  [Notice \(handling\)](#)
- ?  [Packaging](#)
- ?  [Minimum Quantity\[Supplementation\]](#)

Minimum Quantity

| | |
|---------------------|------|
| 180mm Paper Tape | |
| 180mm Embossed Tape | 3000 |
| 330mm Paper Tape | |
| 330mm Embossed Tape | 9000 |
| Bulk Case | |
| Bulk(Bag) | 500 |
| Ammo Pack | |
| 320Reel | |
| Magazine | |
| Box | |

Please approve our product specifications or to transact the approval sheet for product specifications before ordering. Please read rating and !Cautions first.
Product specifications in this catalog are as of January 2008.

All products and company names herein are trademarks or registered trademarks of their respective owners.