

Timing Device > CERALOCK (MHz) > Series

How to check EU RoHS Compliance of Our Products is [here](#).

<a href="#">Product Lifecycle Stage</a>	in Production
<a href="#">Recommended Rank</a>	Preferred

### Specifications

Global Part Number	CSTCE_G
Previous Part Number	
Oscillating Frequency	8.00 to 13.99MHz
Initial Tolerance	±0.5%
Frequency Shift by Temperature	±0.2%
Operating Temperature Range	-20 to 80...
Wash	Not Available
Ultrasonic Wash	Not Available
Capacitor	Built in
Frequency Tolerance	Available in ±0.3%
Use	
Applications	For consumer electronics

### Details

- [Part Numbering](#)
- [Appearance](#)
- [Dimensions](#)
- [Features, Applications](#)
- [Frequency Temperature Characteristics](#)
- [Standard Land Patterns](#)
- [Notice](#)
- [Packaging](#)
- [Minimum Quantity \(Supplementation\)](#)

### Minimum Quantity

180mm Paper Tape	
180mm Embossed Tape	3000
330mm Paper Tape	
330mm Embossed Tape	9000
Bulk Case	
Bulk(Bag)	500
Ammo Pack	
320Reel	
Magazine	
Box	

Please approve our product specifications or to transact the approval sheet for product specifications before ordering.  
 Please read rating and !Cautions first.  
 Product specifications in this catalog are as of March 2015  
 Please make sure to read the Murata's [Product Policy](#) ,too.

All products and company names herein are trademarks or registered trademarks of their respective owners.

UP ^