


Product Search Data Sheet

CSTCC2M00G53A-B0

Note: This datasheet may be out of date. <u>Please download the latest datasheet of CSTCC2M00G53A-B0 from the official website of Murata</u> <u>Manufacturing Co., Ltd.</u> http://www.murata.com/en-us/products/productdetail?partno=CSTCC2M00G53A-B0



Appearance & Shape



Features

MURATA's frequency adjustment and package technology expertise has enabled the development of the chip

CERALOCK(R) with built-in load capacitors. This diverse series owes its development to MURATA's original mass production techniques and high reliability, and has achieved importance in the worldwide automotive market.

Features

1. The series has high reliability and is available for a wide temperature range.

- 2. Oscillation circuits do not require external load capacitors.
- 3. The series is available in a wide frequency range.
- 4. The resonators are extremely small and have a low profile.
- 5. No adjustment is necessary for oscillation circuits.



Automotive Usage	Powertrain/Safety
Other Usage	Automotive

Packaging Information

Packaging	Specifications	Minimum Order Quantity
-B0	Bulk	500

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Downloaded from Arrow.com.



Product Search Data Sheet

CSTCC2M00G53A-B0

Note: This datasheet may be out of date. Please download the latest datasheet of CSTCC2M00G53A-B0 from the official website of Murata Manufacturing Co., Ltd. http://www.murata.com/en-us/products/productdetail?partno=CSTCC2M00G53A-B0

Specifications

Shape	SMD
Frequency	2.000MHz
Frequency Tolerance	±0.5%
Operating Temperature Range	-40°C to 125°C
Frequency Shift by Temperature	±0.4%
Frequency Aging	±0.3%
Wash	avai able
Resonant Impedance	80Ω
Built-in Load Capacitance	15pF

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

muKata

2 of 3


Product Search Data Sheet



CSTCC2M00G53A-B0

Note: This datasheet may be out of date. <u>Please download the latest datasheet of CSTCC2M00G53A-B0 from the official website of Murata</u> <u>Manufacturing Co., Ltd.</u> http://www.murata.com/en-us/products/productdetail?partno=CSTCC2M00G53A-B0





Temperature Characteristics

3 of 3

Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

muRata

URL : http://www.murata.com/

Downloaded from Arrow.com.