

CSTCW27M0X51-R0

Note: This datasheet may be out of date.

Please download the latest datasheet of CSTCW27M0X51-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=CSTCW27M0X51-R0










Appearance & Shape







Features

MURATA's package technology expertise has enabled the development of the Chip CERALOCK(R) with built-in load capacitors. High-density mounting can be realized because of the small package and the elimination of the need for an external load capacitor.

Features

- 1. Oscillation circuits do not require external load capacitors.
- 2. Available in a wide frequency range.
- 3. Extremely small and have a low profile.
- 4. No adjustment is necessary for oscillation circuits.



Applications

Other Usage	Consumer/Industrial
-------------	---------------------



Packaging Information

Packaging		Standard Packing Quantity
R0	180mm Embossed Tape	3000

1 of 2

Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of CSTCW27M0X51-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=CSTCW27M0X51-R0

CSTCW27M0X51-R0



Specifications

Product Type	Ceramic Resonator	
Product Type	(CERALOCK)	
Series	CSTCW_X	
Frequency	27.000MHz	
Frequency Tolerance	+/-0.50% max.	
Operating Temperature	-20°C~80°C	
Range		
Frequency Shift by	+/-0.20% max.	
Temperature	, 0.20 %	
Frequency Aging	+/-0.10% max.	
Resonant Impedance (R1)	60ohm max.	
Built-in Load Capacitance	6pF	
(CL1/CL2)		
Shape	SMD	
Wash	Not available	
L x W (size)	2.5x2.0mm	
Mass	32mg	

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

