

Timing Device > CERALOCK (MHz) > Series











How to check EU RoHS Compliance of Our Products is [here](#).

<a href="#">Product Lifecycle Stage</a>	in Production
<a href="#">Recommended Rank</a>	Preferred

**Specifications**

**Details**

Global Part Number	CSTCW_X
Previous Part Number	CSTCW_MX
Oscillating Frequency	20.01 to 70.00MHz
Initial Tolerance	±0.5%
Frequency Shift by Temperature	±0.2%
Operating Temperature Range	-20 to 80...
Wash	Not Available
Ultrasonic Wash	Not Available
Capacitor	Built in
Frequency Tolerance	Available in ±0.3%,±0.2%
Use	
Applications	For consumer electronics

-  [Part Numbering](#)
-  [Appearance](#)
-  [Dimensions](#)
-  [Features, Applications](#)
-  [Frequency Temperature Characteristics](#)
-  [Basic Oscillation Circuit](#)
-  [Standard Land Patterns](#)
-  [Notice](#)
-  [Packaging](#)
-  [Minimum Quantity \(Supplementation\)](#)

**Minimum Quantity**

180mm Paper Tape	
180mm Embossed Tape	3000
330mm Paper Tape	
330mm Embossed Tape	9000
Bulk Case	
Bulk(Bag)	500
Ammo Pack	
320Reel	
Magazine	
Box	

**Please approve our product specifications or to transact the approval sheet for product specifications before ordering.**  
**Please read rating and !Cautions first.**  
**Product specifications in this catalog are as of March 2015**  
**Please make sure to read the Murata's [Product Policy](#) ,too.**

All products and company names herein are trademarks or registered trademarks of their respective owners.

UP ^