

OVATOR IN ELECTRONICS

CSTCC3M58G53A-R0

Note: This datasheet may be out of date

Please download the latest datasheet of CSTCC3M58G53A-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=CSTCC3M58G53A-R0










Appearance & Shape







Features

MURATA's frequency adjustment and package technology expertise has enabled the development of the chip CERALOCK(R) with built-in load capacitors. This diverse series owes its development to MURATA's original mass production techniques and high reliability, and has achieved importance in the worldwide automotive market.

Features

- 1. The series has high reliability and is available for a wide temperature range.
- 2. Oscillation circuits do not require external load capacitors.
- 3. The series is available in a wide frequency range.
- 4. The resonators are extremely small and have a low profile.
- 5. No adjustment is necessary for oscillation circuits.



Applications

Automotive Usage	Powertrain/Safety
Other Usage	Automotive



Packaging Information

Packaging	Specifications	Standard
		Packing
		Quantity
R0	180mm Embossed Tape	2000

1 of 2

Attentior

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: This datasheet may be out of date. $Please\ download\ the\ latest\ data sheet\ of\ CSTCC3M58G53A-R0\ from\ the\ official\ website\ of\ Murata$ Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=CSTCC3M58G53A-R0

CSTCC3M58G53A-R0



Specifications

Due don't Tour	Ceramic Resonator	
Product Type	(CERALOCK)	
Series	CSTCC_G_A	
Frequency	3.580MHz	
Frequency Tolerance	+/-0.50% max.	
Operating Temperature Range	-40°C~125°C	
Frequency Shift by		
. , ,	+/-0.40% max.	
Temperature		
Frequency Aging	+/-0.30% max.	
Resonant Impedance (R1)	50ohm max.	
Built-in Load Capacitance	15pF	
(CL1/CL2)		
Shape	SMD	
Wash	available	
L x W (size)	7.2x3.0mm	
Mass	82mg	

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

