Products

TDK Worldwide

Search by Part Number or Keywo Search

Application Guides Technical Support Tech Library Contact Environment

🎢 🖒 Pri 🖒 Vc 🖒 Te 🖒 Chip NTC Thermistors (Protection Device) 🖒 Detailed Information

News

Chip NTC Thermistors (Protection Device)

Catalog

Product Top Page NTCG164L	·	Search by Characteristics	Cross Reference	Catalog	Tech Notes	Technical Support Tools	ACH Halogen Free Free Free
Applications	Automotive Grade				×	PDF file of this page	L
Features	AEC-Q200 AEC-Q200			La		Buy Now	
				Images are for reference only and show exemplary products.	ice only	Contact	
Status	Production			Documents RT Sheet			
Brand T	DK					5.1551	

Size			
Length(L)	1.60mm ±0.10mm		
Width(W)	0.80mm ±0.10mm		
Thickness(T)	0.80mm ±0.10mm		
Terminal Width(B)	0.20mm Min.		
Recommended Land Pattern (PA)	0.70mm ±0.10mm		
Recommended Land Pattern (PB)	0.70mm ±0.10mm		
Recommended Land Pattern (PC)	0.70mm ±0.10mm		

Electrical Characteristics	
Resistance [at 25°C]	100kΩ
Resisltance Tolerance	±5%
B value (Typ.) [25/50°C]	4485K
B value (Typ.) [25/85°C]	4550K
B value (Typ.) [25/100°C]	4573K
B value Tolerance	±3%
Max. Electric Power [at 25°C] ?	100mW
Permissive Operating Current [at 25°C] ?	100μΑ
Thermal Dissipation Constant [at 25°C] ?	1mW/°C 1mW/K

Other	
Max. Operating Temperature	125°C
Soldering Method	Reflow
UL File No.	E250289
AEC-Q200	Yes
Packing	Punched (Paper)Taping [180mm Reel]
Package Quantity	4000pcs
Weight	0.005g

Products

» Search by Part No. » Search by Characteristics » Distributor Inventory Check

» Capacitors

» Anechoic Chambers and Radio Wave Absorbers

» Inductors (Coils)

» Power Supplies

» EMC Components

Downloaded from Arrow.com.

» Magnets » Flash Storages

» RF / SAW Components and Modules » Voltage / Current / Temperature Protection Devices

» Wireless Charging

Technical Support Tech Library Environment Contact

Application Guides

News

» Sensors and Sensor Systems

» Ceramic Switching / Heating, Piezo Components and

Buzzers

» Transformers

» Ferrites and Accessories

» Noise Suppressing / Magnetic Sheet

» FA Systems

» Transparent Conductive Film

» Micro Modules (Substrates with Built-in ICs, Products Utilizing with SESUB)

» Solar Cells

» Biosensor

Home

About TDK

TDK Worldwide

Terms of Use

Copyright(c) 1996-2017 TDK Corporation. All rights reserved. TDK logo is a trademark or registered trademark of TDK Corporation.

