

Search

Search by keywords

Enter Keyword or Product Number

SEARCH

Expert Search >

Stock Search

Datasheet
Shortcut

Part No.

Specifications

Parts Inventory

Related Documents

Part No.

Specifications

ECA2GM220E

Part No: ECA2GM220E



Contact Us











- > [Sales & Support](#)
- > [Send Inquiry](#)

Specifications


Item	Performance characteristics
Body shape	Radial lead type
Polarity type	Polar
Rated voltage	400 V
Capacitance	22 micro F
Category temperature range	-25 to 85 Cel
Body diameter	12.5 mm
Body length	25 mm
Rated ripple current-1 (freq.)	120 Hz
Rated ripple current-1	215 mA
Endurance	2000 h
Forming & packaging feature	Bulk (the lead wire or terminal of snap-in type forming), bag packing
Tolerance on capacitance	-20 to 20 %
Tangent of loss angle (max.)	0.2
Leakage current (max.)	538 micro A
Lead (terminal) pitch	5 mm
Rated ripple current-1 (unit)	mA r.m.s. (root mean square)
Impedance-1 (frequency)	n/a
Impedance-1 (max. value)	n/a

Item	Performance characteristics
E.S.R.-2 (freq.)	n/a
E.S.R.-2 (max. value)	n/a
Appearance	P.E.T. sleeve sheathing (metal case)
Quantity (min. packaging unit)	200 PCS.
Weight (Typ.)	4.7 g

Related Documents

	Data Sheet
	Catalog
	Country of Origin
	Explanation of Part Numbers
	Letter for Certificate of Compliance to EU RoHS Directive
	Packaging Specifications
	Product system
	Products Catalog (Radial Lead Type Aluminum Electrolytic)
	Report of Confirmation of EU REACH 16th SVHC
	Safety Precautions

 Print

 Back to top

Area / Country

[About Us](#) | [Contact Us](#) | [Site Map](#) | [Press Room](#) | [Privacy Policy](#) | [Terms of Service](#)



 Download the App

 Subscribe

Copyright ©2018 Panasonic Corporation of North America. All Rights Reserved.