Note: This datasheet may be out of date.

Please download the latest datasheet of GRM21BR72A393MA01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=GRM21BR72A393MA01%23

"#" indicates a package specification code.

GRM21BR72A393MA01#
















< List of part numbers with package codes > GRM21BR72A393MA01K GRM21BR72A393MA01L



Appearance & Shape







References

Packaging	Specifications	Standard Packing Quantity
К	330Embossed Tape	10000
L	180Embossed Tape	3000

Mass (typ.)	
φ180mm Reel	102g

1 of 2

Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



GRM21BR72A393MA01#

Note: This datasheet may be out of date.

 $Please\ download\ the\ latest\ data sheet\ of\ GRM21BR72A393MA01\#\ from\ the\ official\ website\ of\ Muratangle and the statest of\ Muratangle and\ Muratangle$ Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=GRM21BR72A393MA01%23

"#" indicates a package specification code.



Specifications

Length	2.0±0.1mm
Width	1.25±0.1mm
Thickness	1.25±0.1mm
Capacitance	39000pF ±20%
Distance between external terminals g	0.7mm min.
External terminal size e	0.2 to 0.7mm
Operating Temperature Range	-55°C to 125°C
Rated Voltage	100Vdc
Size code in inch(mm)	0805 (2012M)
Capacitance change rate	±15.0%
Temperature characteristics (complied standard)	X7R(EIA)
Temperature range of temperature characteristics	-55°C to 125°C

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

