



MLP2520HR47MT0S1













Size	
Length(L)	2.50mm ±0.15mm
Width(W)	2.00mm ±0.15mm
Thickness Height	0.85mm ±0.15mm
Recommended Land Pattern (A)	0.70mm Nom.
Recommended Land Pattern (B)	1.40mm Nom.
Recommended Land Pattern (C)	2.00mm Nom.

Electrical Characteristics		
Inductance	470nH ±20% at 2MHz	
Rated Current (L Change) [Typ.]		
Rated Current (L Change) [Max.]		
Rated Current (Temperature Rise) [Typ.]		
Rated Current (Temperature Rise) [Max.]	2.1A (40°C Rise)	
DC Resistance [Typ.]	44mΩ	
DC Resistance [Max.]	57.2mΩ	
Self Resonant Frequency [Min.]		
Self Resonant Frequency [Typ.]		
Q [Min.]		
Q [Typ.]		

Other	
Operating Temp. Range (Including Self-Temp. Rise)	-40 to 125°C
Soldering Method	Reflow
	Iron Soldering
AEC-Q200	No
Packing	Blister (Plastic)Taping [180mm Reel]
Package Quantity	3000pcs
Weight	0.015g

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.



MLP2520HR47MT0S1














Characteristic Graphs(This is reference data, and does not guarantee the products characteristics.)











 $^{!\ \}mbox{Images}$ are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.





MLP2520HR47MT0S1











Associated Images





[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.