SMD / SMT Inductors (Coils) SLF6045T-220M1R1-3PF

Applications	Commercial Grade	_
Feature	Wire Wound Shield Magnetic Shield Ferrite Core Ferrite Core	
Series Type	SLF	
Status	Production	
Brand	ток	m

Size		
Length(L)	6.00mm ±0.20mm	
Width(W)	6.00mm ±0.20mm	
Thickness Height	4.50mm ±0.30mm	
Recommended Land Pattern (A)	1.50mm Nom.	
Recommended Land Pattern (B)	4.00mm Nom.	
Recommended Land Pattern (C)	2.20mm Nom.	


Electrical Characteristics			
Inductance	22µH ±20% at 100kHz		
Rated Current (L Change) [Typ.]			
Rated Current (L Change) [Max.]	1.1A (10% Down)		
Rated Current (Temperature Rise) [Typ.]	1.8A (30°C Rise)		
Rated Current (Temperature Rise) [Max.]			
DC Resistance [Typ.]	82mΩ		
DC Resistance [Max.]	98.4mΩ		
Self Resonant Frequency [Min.]			
Self Resonant Frequency [Typ.]			
Q [Min.]			
Q [Typ.]			

Other		
Operating Temp. Range (Including Self-Temp. Rise)	-40 to 105°C	
Coldering Mathed	Reflow	
Soldering Method	Iron Soldering	
AEC-Q200	NO	
Packing	Embossed (Plastic)Taping [330mm Reel]	
Package Quantity	1000pcs	
Weight	0.4g	

[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.


Characteristic Graphs(This is reference data, and does not guarantee the products characteristics.)



! Images are for reference only and show exemplary products.

! This PDF document was created based on the data listed on the TDK Corporation website.


Characteristic Graphs(This is reference data, and does not guarantee the products characteristics.)



! Images are for reference only and show exemplary products.

! This PDF document was created based on the data listed on the TDK Corporation website.

Associated Images



! Images are for reference only and show exemplary products.

! This PDF document was created based on the data listed on the TDK Corporation website.