

Note: This datasheet may be out of date. Please download the latest datasheet of NFZ15SG771SN10# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=NFZ15SG771SN10%23

"#" indicates a package specification code.

# NFZ15SG771SN10#







< List of part numbers with package codes > NFZ15SG771SN10B NFZ15SG771SN10D



### Appearance & Shape













#### **Features**

- 1. NFZ15SG series is designed for noise suppression of audio lines such as class D amplifier. This product can suppress noise about the range from 700MHz to 2GHz without distorting audio waveform. We have set the impedance specify frequency as 900MHz in this reason.
- 2. The nickel barrier structure of the external electrodes provides excellent solder heat resistance.
- 3. Low DC resistance of NFZ15SG series meets large current. Its rated current ranges from 0.27A to 1.1A
- 4. Meets 85°C maximum operating temperature.



## **Applications**

Other Usage	For general



## **Packaging Information**

Packaging	Specifications	Standard
		Packing
		Quantity
В	Bulk(Bag)	1000
D	180mm Paper Tape	10000

1 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





# NFZ15SG771SN10#

Note: This datasheet may be out of date.

Please download the latest datasheet of NFZ15SG771SN10# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=NFZ15SG771SN10%23

"#" indicates a package specification code.



# **Specifications**

Shape	SMD
Size Code (in inch)	0402
Length	1.0mm
Length Tolerance	±0.05mm
Width	0.5mm
Width Tolerance	±0.05mm
Thickness	0.5mm
Thickness Tolerance	±0.05mm
Operating Temperature Range	-40°C to 85°C
Mass(typ.)	0.001g
Number of Circuit	1
Rated Current (at 85°C)	500mA
DC Resistance(max.)	0.5Ω
DC Resistance	0.35Ω (Typ.)
Impedance (at 900MHz)	770Ω
Impedance (at 900MHz) Tolerance	(Тур.)
Impedance (at 1.7GHz)	900Ω
Impedance (at 1.7GHz) Tolerance	(Тур.)
Size Code (in mm)	1005

2 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




# NFZ15SG771SN10#


Note: This datasheet may be out of date.


Please download the latest datasheet of NFZ15SG771SN10# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=NFZ15SG771SN10%23

"#" indicates a package specification code.







Impedance-Frequency Characteristics

**Equivalent Circuit** 

3 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

