

Note: This datasheet may be out of date. Please download the latest datasheet of BLM18BB151SH1# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=BLM18BB151SH1%23


"#" indicates a package specification code.


BLM18BB151SH1#

In Production AEC-Q200 RoHS REACH

< List of part numbers with package codes > BLM18BB151SH1B BLM18BB151SH1D BLM18

BLM18BB151SH1J







Packaging Information

Packaging	Specifications	Standard Packing Quantity
В	Bulk(Bag)	1000
D	180mm Paper Tape	4000
J	330mm Paper Tape	10000



(in mm)

Features

The chip ferrite beads BLM series is designed to function nearly as a resistor at noise frequencies, which greatly reduces the possibility of resonance and leaves signal wave forms undistorted.

BLM series is effective in circuits without stable ground lines because BLM series does not need a connection to ground.

The nickel barrier structure of the external electrodes provides excellent solder heat resistance. BLM_B series can minimize attenuation of the signal waveform due to its sharp impedance characteristics. Various impedances are available to match signal frequency.

 Applications

 Automotive Usage
 Powertrain/Safety

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





BLM18BB151SH1#

Note: This datasheet may be out of date. Please download the latest datasheet of BLM18BB151SH1# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=BLM18BB151SH1%23

"#" indicates a package specification code.



Specifications

Shape	SMD	
Size Code (in inch)	0603	
Length	1.6mm	
Length Tolerance	±0.15mm	
Width	0.8mm	
Width Tolerance	±0.15mm	
Thickness	0.8mm	
Thickness Tolerance	±0.15mm	
Operating Temperature Range	-55°C to 125°C	
Mass(typ.)	0.005g	
Number of Circuit	1	
Rated Current (at 85°C)	450mA	
Rated Current (at 125°C)	450mA	
DC Resistance(max.)	0.37Ω	
Impedance (at 100MHz)	150Ω	
Impedance (at 100MHz) Tolerance	±25%	
Size Code (in mm)	1608	

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.






BLM18BB151SH1#


Note: This datasheet may be out of date. Please download the latest datasheet of BLM18BB151SH1# from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en/products/productdetail?partno=BLM18BB151SH1%23

"#" indicates a package specification code.









Impedance-Frequency Characteristics

Equivalent Circuit

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.