## SMD / SMT Inductors (Coils) VLF252010MT-100M

| Applications  | Commercial Grade   |
|---------------|--|
|               | Wire Wound Wire Wound  |
| Feature       | Shield Magnetic Shield   |
|               | Ferrite Core   |
| Series   Type | VLF-M  |
| Status        | A Obsolete   |
|               | Recommended Alternate Part No. : <u>VLS252010HBX-100M-1</u> (Interchangeability is |
|               | not guaranteed.)   |
|               | Discontinue Issue Date : May.18, 2017  |
|               | Last Purchase Order Date : Mar.31, 2021  |
|               | Last Shipment Date : Sep.30, 2021  |
| Brand         | ток  |


| Size                         |                |  |
|------------------------------|----------------|--|
| Length(L)                    | 2.50mm ±0.20mm |  |
| Width(W)                     | 2.00mm ±0.20mm |  |
| Thickness   Height           | 1.00mm Max.    |  |
| Recommended Land Pattern (A) | 0.75mm Nom.    |  |
| Recommended Land Pattern (B) | 0.60mm Nom.    |  |
| Recommended Land Pattern (C) | 1.30mm Nom.    |  |

| Electrical Characteristics              |                   |  |  |  |
|---|-------------------|--|--|--|
| Inductance                              | 10µH ±20% at 1MHz |  |  |  |
| Rated Current (L Change) [Typ.]         | 440mA (30% Down)  |  |  |  |
| Rated Current (L Change) [Max.]         | 390mA (30% Down)  |  |  |  |
| Rated Current (Temperature Rise) [Typ.] | 660mA (40°C Rise) |  |  |  |
| Rated Current (Temperature Rise) [Max.] |                   |  |  |  |
| DC Resistance [Typ.]                    | 490mΩ             |  |  |  |
| DC Resistance [Max.]                    | 590mΩ             |  |  |  |
| Self Resonant Frequency [Min.]          |                   |  |  |  |
| Self Resonant Frequency [Typ.]          |                   |  |  |  |
| Q [Min.]                                |                   |  |  |  |
| Q [Typ.]                                |                   |  |  |  |

| 01  | ther                                  |
|---|---------------------------------------|
| Operating Temp. Range (Including Self-Temp. Rise)   | -40 to 105°C                          |
| Soldering Method  | Reflow                                |
| AEC-Q200  | NO                                    |
| Packing   | Embossed (Plastic)Taping [180mm Reel] |
| Images are for reference only and show exemplary products.<br>Package Quantity<br>I This PDF document was created based on the data listed on the TDK Corporation website | 2000pcs                               |
| Weight  | 0.017g                                |

Copyright(c) TDK Corporation. All rights reserved. Downloaded from Arrow.com.

## Characteristic Graphs(This is reference data, and does not guarantee the products characteristics.)




! Images are for reference only and show exemplary products.

! This PDF document was created based on the data listed on the TDK Corporation website.

! All specifications are subject to change without notice.

Characteristic Graphs(This is reference data, and does not guarantee the products characteristics.)




! Images are for reference only and show exemplary products.

! This PDF document was created based on the data listed on the TDK Corporation website.

! All specifications are subject to change without notice.

RoHS Reach Halogen Free Pb Free

## Associated Images



! Images are for reference only and show exemplary products.

! This PDF document was created based on the data listed on the TDK Corporation website.

 $! \ \mbox{All specifications} \ \mbox{are subject to change without notice}.$