

BLM03HG102SN1#

Note: This datasheet may be out of date. Please download the latest datasheet of BLM03HG102SN1# from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en/products/productdetail?partno=BLM03HG102SN1%23


"#" indicates a package specification code.

In Production RoHS REACH

< List of part numbers with package codes > BLM03HG102SN1B BLM03HG102SN1D B

BLM03HG102SN1J





(in mm)

Applications

Other Usage

For general



Packaging Information

| Packaging | Specifications | Standard Packing Quantity |
|-----------|------------------|---------------------------------|
| В | Bulk(Bag) | 1000 |
| D | 180mm Paper Tape | 15000 |
| J | 330mm Paper Tape | 50000 |



Features

- 1. Horizontal winding inner coil structure enables low storage capacitance which result to high noise suppression performance up to 1GHz frequency range.
- 2. The small size of BLM03H series (0.6x0.3mm) is suitable for noise suppression in small equipment such as cellular phones.

Application

- 1. Intra-system EMC in cellular phones.
- 2. EMI countermeasure of cellular phones.
- 3. Keyed carrier noise countermeasure for cellular phones.
- 4. EMI countermeasure of NotePC/MID, and DSC

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

- without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





BLM03HG102SN1#

Note: This datasheet may be out of date. Please download the latest datasheet of BLM03HG102SN1# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=BLM03HG102SN1%23

"#" indicates a package specification code.



Specifications

| Shape | SMD |
|------------------------------------|----------------|
| Size Code (in inch) | 0201 |
| Length | 0.6mm |
| Length Tolerance | ±0.03mm |
| Width | 0.3mm |
| Width Tolerance | ±0.03mm |
| Thickness | 0.3mm |
| Thickness Tolerance | ±0.03mm |
| Operating Temperature Range | -55°C to 125°C |
| Mass(typ.) | 0.3mg |
| Number of Circuit | 1 |
| Rated Current (at 85°C) | 125mA |
| Rated Current (at 125°C) | 125mA |
| DC Resistance(max.) | 2.6Ω |
| Impedance (at 100MHz) | 1000Ω |
| Impedance (at 100MHz) Tolerance | ±25% |
| Impedance (at 1GHz) | 1800Ω |
| Impedance (at 1GHz) Tolerance | ±40% |
| Size Code (in mm) | 0603 |

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.






BLM03HG102SN1#


Note: This datasheet may be out of date. Please download the latest datasheet of BLM03HG102SN1# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=BLM03HG102SN1%23

"#" indicates a package specification code.







Impedance-Frequency Characteristics

Equivalent Circuit

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



3 of 3