Note: This datasheet may be out of date.

Please download the latest datasheet of NFZ2MSD101SZ10# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NFZ2MSD101SZ10%23

"#" indicates a package specification code.

NFZ2MSD101SZ10#










< List of part numbers with package codes > NFZ2MSD101SZ10L



Appearance & Shape







Features

- 1. NFZ2MSD_SZ is a noise filter designed for noise suppression of audio lines in car navigation systems, car radios, and other automotive information equipment.
- Can be used in high current circuits due to its low DC resistance.
- 3. Low magnetic flux leakage with magnetically shielded structure.
- 4. Meets 125°C maximum operating temperature.

Applications

Automotive Usage

Infotainment



Packaging Information

Packaging	Specifications	Standard Packing Quantity
L	180mm Embossed Tape	3000

1 of 3

Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



NFZ2MSD101SZ10#

Note: This datasheet may be out of date.

Please download the latest datasheet of NFZ2MSD101SZ10# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NFZ2MSD101SZ10%23

"#" indicates a package specification code.



Specifications

Shape	SMD
Size Code (in inch)	0806
Length	2 0mm
Longin	2.011111
Length Tolerance	±0.2mm
Width	1.6mm
Width Tolerance	±0.2mm
Thickness	1.2mm
Thickness Tolerance	max.
Operating Temperature Range	-40°C to 85°C
Operating Temperature Range (Self-temperature rise is included)	-40°C to 125°C
Mass(typ.)	0.0188g
Number of Circuit	1
Rated Current (at 85°C)	5.2A
DC Resistance(max.)	18mΩ
DC Resistance	18mΩ max.
Impedance (at 10MHz)	9Ω
Impedance (at 10MHz) Tolerance	±30%
Impedance (at 100MHz)	100Ω
Impedance (at 100MHz) Tolerance	(Тур.)
Size Code (in mm)	2016

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Please download the latest datasheet of NFZ2MSD101SZ10# from the official website of Murata

Manufacturing Co., Ltd.


http://www.murata.com/en/products/productdetail?partno=NFZ2MSD101SZ10%23

Note: This datasheet may be out of date.


"#" indicates a package specification code.

NFZ2MSD101SZ10#






Max. current (DC, AC) as function of product temperature (derating curve).



Impedance-Frequency Characteristics



Derating of Rated Current

Equivalent Circuit

3 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.