


Product Search Data Sheet

NXRT15XH103FA5B030

NRND ROHS REACH

Appearance & Shape



Note: This datasheet may be out of date. Please download the latest datasheet of NXRT15XH103FA5B030 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NXRT15XH103FA5B030



1. NXR series can accurately detect temperature with NCP15 series on the head of parts.

2. The insulation coat with polyulethane on the surface of lead wire : 100VDC.

3. You can choose NTC characteristics from NCP15 series.

4. The resistance drift is small in the reliability test.

5. The production capacity is bigger and NXR is produced in almost all automation line.

6. Adopt to Sb regulation

7. UL/cULcertified product. (UL1434, File No. E137188)

Applications

Limited Usage

Consumer Grade



Packaging Information

Packaging	Specifications	Standard Packing
		Quantity
В	Bulk(Bag)	500

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





NXRT15XH103FA5B030

Note: This datasheet may be out of date. Please download the latest datasheet of NXRT15XH103FA5B030 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NXRT15XH103FA5B030

Specifications

Resistance (25°C)	10kΩ
Resistance Value Tolerance (at 25°C)	±1%
B-Constant (25/50°C)	3380K
B-Constant (25/50°C) Tolerance	±1%
B-Constant(25/80°C) (Reference Value)	3428K
B-Constant(25/85°C) (Reference Value)	3434K
B-Constant(25/100°C) (Reference Value)	3455K
Maximum Operating Current (25°C)	0.16mA
Rated Electric Power (25°C)	13.0mW
Typical Dissipation Constant (25℃)	2.6mW/°C
Operating Temperature Range	-40°C to 125°C
Thermal Time Constant	4s
Lead Shape	Insulation type
Size Code (in mm)	030 = 30mm
Size Code (in inch)	030 = 30mm
Shape	Lead
Mass	0.098g
MSL	Ν

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

- without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Product Search Data Sheet


Note: This datasheet may be out of date. Please download the latest datasheet of NXRT15XH103FA5B030 from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en/products/productdetail?partno=NXRT15XH103FA5B030

NXRT15XH103FA5B030



Product Data





Resistance-Temperature Characteristics

Temperature Tolenrance VS. Temp.

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

- without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



3 of 3