

CA2978: 12-pin ribbon cable for use with DC1613, DC2086

REVISIONS			
REV	DESCRIPTION	APPR	DATE

2X, FLUSH CABLE ENDS, THIS SIDE
(+.02 -.00)

CENTRAL KEY

PIN 1

8.00 ±.25

CENTRAL KEY

PIN 1

1 2X

RED STRIPE (PIN 1)

2 A/R

MODIFICATION OF CONNECTOR CENTRAL KEY:

BEFORE

REMOVE "FRICTION LOCK BUMPS" 2 PLACES.

AFTER

ITEM NO.	QTY REQD	PART OR IDENTIFYING NO.	CAGE CODE	NOMENCLATURE OR DESCRIPTION	MATERIAL SPECIFICATION
2	A/R			CABLE, FLAT RIBBON, 12 COND. 1mm, 28 AWG	
1	2			CONN, 2.00mm IDC, 12 PIN (MODIFICATION OF CENTRAL KEY REQUIRED)	FCI 89361-712LF

PARTS LIST

<p>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON ANGLE ± 1 2 PLACE ± .01 3 PLACE ± .005 INTERPRET DIM AND TOL PER ASME Y14.5M - 1994</p>	APPROVALS		<p>1630 McCarthy Blvd. Milpitas, CA 95035 Ph: (408)432-1900</p>
	PDR DESIGNER	DATE	
	ENGINEER	3/13/09	
	CHECK		
		<p>TITLE: ASSY, CBL, 12 COND. 1MM FLAT RIBBON</p> <p>SIZE A DEMO CA2978 REV. 1</p>	
SCALE = NONE			SHT 1 of 1