

Note: This datasheet may be out of date. Please download the latest datasheet of BLM03HB401SZ1# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=BLM03HB401SZ1%23

"#" indicates a package specification code.


In Production AEC- RoHS REACH

0200

BLM03HB401SZ1#

< List of part numbers with package codes > BLM03HB401SZ1B BLM03HB401SZ1D BLM03HB401SZ1J

Appearance & Shape



Applications

Automotive Usage

Infotainment



Packaging Information

Packaging	Specifications	Standard Packing Quantity
В	Bulk(Bag)	1000
D	180mm Paper Tape	15000
J	330mm Paper Tape	50000



Features

- 1. Horizontal winding inner coil structure enables low storage capacitance which result to high noise suppression performance.
- Effective in LTE range up to 2.6GHz from 700MHz. 2. The small size of BLM03H series (0.6x0.3mm) is
- suitable for noise suppression in small equipment such as cellular phones.

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

- without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





BLM03HB401SZ1#

Note: This datasheet may be out of date. Please download the latest datasheet of BLM03HB401SZ1# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=BLM03HB401SZ1%23

"#" indicates a package specification code.



Specifications

Shape	SMD
Size Code (in inch)	0201
Length	0.6mm
Length Tolerance	±0.03mm
Width	0.3mm
Width Tolerance	±0.03mm
Thickness	0.3mm
Thickness Tolerance	±0.03mm
Operating Temperature Range	-55°C to 125°C
Mass(typ.)	0.3mg
Number of Circuit	1
Rated Current (at 85°C)	125mA
Rated Current (at 125°C)	125mA
DC Resistance(max.)	2.8Ω
Impedance (at 100MHz)	400Ω
Impedance (at 100MHz) Tolerance	±25%
Impedance (at 1GHz)	1850Ω
Impedance (at 1GHz) Tolerance	±40%
Size Code (in mm)	0603

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.






BLM03HB401SZ1#


Note: This datasheet may be out of date. Please download the latest datasheet of BLM03HB401SZ1# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=BLM03HB401SZ1%23

"#" indicates a package specification code.







Impedance-Frequency Characteristics

Equivalent Circuit

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



3 of 3