

Wireless Power Transfer / NFC Antennas Low Loss Sheets (Shield)

[Product Top Page](#) [Product List](#) [Cross Reference](#) [Catalog](#) [Tech Notes](#) [Technical Support Tools](#)

IFL04-200NB300X200



Features [Low Loss](#) Low loss

Series IFL04

Status Production (Not Recommended for New Design)
Recommended Alternate Part No. : [IFL04-200ND300X200](#)

Images are for reference only and show exemplary products.

PDF file of this page

Contact

Documents

Catalog

Size	
Length	300mm Nom.
Width	200mm Nom.
Magnetic Material Thickness	0.2mm Nom.
Overall Thickness	0.22mm Nom.
Electrical Characteristics	
Relative Permeability	45 at 13.56MHz
Surface Resistivity (Min.)	10kΩ / square
Thermal Conductivity	1.5W/m
Other	
Operating Temp. Range	-40 to 85°C
Double Sided Tape	Yes
Delivery Method	Sheet
Flame Retardant Standard	

Products

- » Search by Part No. » Search by Characteristics » Distributor Inventory Check
- » Capacitors
- » Inductors (Coils)
- » EMC Components
- » RF Components and Modules
- » Voltage / Current / Temperature Protection Devices
- » Sensors and Sensor Systems
- » Ceramic Switching / Heating, Piezo Components, Buzzers and Microphones
- » Transformers
- » Ferrites and Accessories
- » Noise Suppressing / Magnetic Sheet
- » Anechoic Chambers and Radio Wave Absorbers
- » Power Supplies
- » Magnets
- » Flash Storages
- » Wireless Power Transfer
- » FA Systems
- » Transparent Conductive Film
- » Micro Modules (Substrates with Built-in ICs, Products Utilizing with SESUB)
- » Solar Cells
- » Biosensor

Application Guides

- » Technical Support
- » Tech Library
- » Environment
- » Contact
- » News
- » Home

About TDK

TDK Worldwide

