

Product Search Data Sheet

NFZ2MSD301SZ10#


In Production AEC-Q200 RoHS REACH

< List of part numbers with package codes > NFZ2MSD301SZ10L



### Appearance & Shape







.0.5±0.3

(in mm)

1.2 max.

# Applications Automotive Usage Infotainment

# Packaging Information

Packaging	Specifications	Standard Packing Quantity
L	180mm Embossed Tape	3000

Note: This datasheet may be out of date. Please download the latest datasheet of NFZ2MSD301SZ10# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NFZ2MSD301SZ10%23

"#" indicates a package specification code.

Features

1. NFZ2MSD\_SZ is a noise filter designed for noise suppression of audio lines in car navigation systems, car radios, and other automotive information equipment.

- 2. Can be used in high current circuits due to its low DC resistance.
- 3. Low magnetic flux leakage with magnetically shielded structure.
- 4. Meets 125°C maximum operating temperature.

1 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Rata Product Search Data Sheet

# NFZ2MSD301SZ10#

Note: This datasheet may be out of date. Please download the latest datasheet of NFZ2MSD301SZ10# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NFZ2MSD301SZ10%23

"#" indicates a package specification code.



## Specifications

Shape	SMD
Size Code (in inch)	0806
Length	2.0mm
Length Tolerance	±0.2mm
Width	1.6mm
Width Tolerance	±0.2mm
Thickness	1.2mm
Thickness Tolerance	max.
Operating Temperature Range	-40°C to 85°C
Operating Temperature Range (Self-temperature rise is included)	-40℃ to 125℃
Mass(typ.)	0.0188g
Number of Circuit	1
Rated Current (at 85°C)	3.8A
DC Resistance(max.)	26mΩ
DC Resistance	26mΩ max.
Impedance (at 10MHz)	21Ω
Impedance (at 10MHz) Tolerance	±30%
Impedance (at 100MHz)	300Ω
Impedance (at 100MHz) Tolerance	(Тур.)
Size Code (in mm)	2016

2 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

- without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Product Search Data Sheet

# NFZ2MSD301SZ10#


Note: This datasheet may be out of date. Please download the latest datasheet of NFZ2MSD301SZ10# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NFZ2MSD301SZ10%23


"#" indicates a package specification code.



## **Product Data**




Max. current (DC, AC) as function of product temperature (derating curve).



#### Impedance-Frequency Characteristics

#### Derating of Rated Current



Equivalent Circuit

3 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

