

Product Search Data Sheet


LFD21829MDKED859

In Production Recommended RoHS REACH



Packaging Information

Packaging	Specifications	Standard Packing Quantity
-	180mm Embossed Tape	4000



Adiplexer branching low and high band.

- 1. Low insertion loss.
- 2. Small size, low-profiled and light weight.
- 3. Absolutely no adjustment required.
- 4. Reflow solderable.

1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Note: This datasheet may be out of date. Please download the latest datasheet of LFD21829MDKED859 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=LFD21829MDKED859



LFD21829MDKED859

Note: This datasheet may be out of date. Please download the latest datasheet of LFD21829MDKED859 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=LFD21829MDKED859

Specifications

Applications	WLAN
Center Frequency(f1)	829.00MHz
Frequency Range(f1)	698.00MHz to 960.00MHz
Center Frequency(f2)	2200.00MHz
Frequency Range(f2)	1710.00MHz to 2690.00MHz
Insertion Loss I)(in f1)	0.40dB max. (at 25℃)
Insertion Loss II)(in f1)	0.50dB max. (-40 to +85°C)
Insertion Loss I)(in f2)	0.55dB max. (at 25℃)
Insertion Loss II)(in f2)	0.65dB max. (-40 ~ +85°C)
Attenuation(in f2)	23.0dB min.
Attenuation(in f1)	20.0dB min.
VSWR{P1}(in f1)	1.40 max.
VSWR{P2}(in f2)	2.10 max.
VSWR{P3}(in f1,f2)	(f1)1.40 max., (f2)2.10 max.
Power Capacity	3W
Operating Temperature Range	-40°C to 85°C
L x W (size)	2.00x1.25mm
Thickness(max.)	1.0mm

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

