



N-Channel 20-, 30-, 40-V (D-S) MOSFETs

PRODUCT SUMMARY				
Part Number	$V_{(BR)DSS}$ Min (V)	$r_{DS(on)}$ Max (Ω)	$V_{GS(th)}$ (V)	I_D (A)
TN0201L	20	1.2 @ $V_{GS} = 10$ V	0.5 to 2	0.64
TN0401L	40	1.2 @ $V_{GS} = 10$ V	0.5 to 2	0.64
VN0300L	30	1.2 @ $V_{GS} = 10$ V	0.8 to 2.5	0.64
VN0300LS	30	1.2 @ $V_{GS} = 10$ V	0.8 to 2.5	0.67

FEATURES


- Low On-Resistance: 0.85 Ω
- Low Threshold: 1.4 V
- Low Input Capacitance: 38 pF
- Fast Switching Speed: 9 ns
- Low Input and Output Leakage

BENEFITS

- Low Offset Voltage
- Low-Voltage Operation
- Easily Driven Without Buffer
- High-Speed Circuits
- Low Error Voltage

APPLICATIONS

- Direct Logic-Level Interface: TTL/CMOS
- Drivers: Relays, Solenoids, Lamps, Hammers, Displays, Memories, Transistors, etc.
- Battery Operated Systems
- Solid-State Relays



Top View

TN0201L
TN0401L
VN0300L

Device Marking
Front View

TN0201L

"S" TN
0201L
xxyy


TN0401L

"S" TN
0401L
xxyy

VN0300L

"S" VN
0300L
xxyy

"S" = Siliconix Logo
xxyy = Date Code



Top View

VN0300LS

Device Marking
Front View

VN0300LS

"S" VN
0300LS
xxyy

"S" = Siliconix Logo
xxyy = Date Code

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)							
Parameter	Symbol	TN0201L	TN0401L	VN0300L	VN0300LS	Unit	
Drain-Source Voltage	V_{DS}	20	40	30	30	V	
Gate-Source Voltage	V_{GS}	± 20	± 20	± 30	± 30		
Continuous Drain Current ($T_J = 150^\circ\text{C}$)	$T_A = 25^\circ\text{C}$	I_D	0.64	0.64	0.64	0.67	A
	$T_A = 100^\circ\text{C}$		0.38	0.38	0.38	0.43	
Pulsed Drain Current ^a	I_{DM}		1.5	1.5	3	3	
Power Dissipation	$T_A = 25^\circ\text{C}$	P_D	0.8	0.8	0.8	0.9	W
	$T_A = 100^\circ\text{C}$		0.32	0.32	0.32	0.4	
Thermal Resistance, Junction-to-Ambient	R_{thJA}		156	156	156	$^\circ\text{C/W}$	
Operating Junction and Storage Temperature Range	T_J, T_{stg}		-55 to 150			$^\circ\text{C}$	

Notes

a. Pulse width limited by maximum junction temperature.

SPECIFICATIONS (T _A = 25 °C UNLESS OTHERWISE NOTED)									
Parameter	Symbol	Test Conditions	Typ ^a	Limits				Unit	
				TN0201L TN0401L		VN0300L VN0300LS			
				Min	Max	Min	Max		
Static									
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0 V I _D = 10 μA	TN0201L	55	20				V
			TN0401L	55	40			30	
Gate-Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 0.25 mA	1.4	0.5	2				
		V _{DS} = V _{GS} , I _D = 1 mA	1.5			0.8	2.5		
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ±20 V			±10				
		V _{DS} = 0 V, V _{GS} = ±30 V					±100	nA	
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 30 V, V _{GS} = 0 V	T _J = 125°C					10	μA
							500		
		V _{DS} = 0.8 x V _{(BR)DSS} , V _{GS} = 0 V			1				
			T _J = 125°C			100			
On-State Drain Current ^b	I _{D(on)}	V _{DS} = 10 V, V _{GS} = 4.5 V	0.9	0.25				A	
		V _{DS} = 10 V, V _{GS} = 10 V	3.5	1		1			
Drain-Source On-Resistance ^b	r _{DS(on)}	V _{GS} = 3.5 V, I _D = 0.05 A	1.8		4			Ω	
		V _{GS} = 5 V, I _D = 0.3 A	1.2				3.3		
		V _{GS} = 4.5 V, I _D = 0.25 A	1.4		2				
		T _J = 125°C	2.6		4				
		V _{GS} = 10 V, I _D = 1 A	0.85		1.2		1.2		
		T _J = 125°C	1.6				2.4		
Forward Transconductance ^b	g _{fs}	V _{DS} = 10 V, I _D = 0.5 A	500	200		200		mS	
Dynamic									
Input Capacitance	C _{iss}	V _{DS} = 15 V, V _{GS} = 0 V, f = 1 MHz	38		60		100	pF	
Output Capacitance	C _{oss}		33		50		95		
Reverse Transfer Capacitance	C _{rss}		8		15		25		
Switching^c									
Turn-On Time	t _{ON}	V _{DD} = 15 V, R _L = 14 Ω I _D ≅ 1 A, V _{GEN} = 10 V R _G = 25 Ω	10		30		30	ns	
Turn-Off Time	t _{OFF}		13		30		30		







Notes

- a. For DESIGN AID ONLY, not subject to production testing..
- b. Pulse test: PW ≤ 300 μs duty cycle ≤ 2%.
- c. Switching time is essentially independent of operating temperature.






VNDQ03



TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)



TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)





Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.