

## CYRS16B256-133FZMB



Status: [Contact Sales](#)

Product Specs	Pricing & Inventory	Packaging/Ordering	Quality and RoHS	Technical Documents
---------------	---------------------	--------------------	------------------	---------------------

CYRS16B256-133FZMB	
Automotive Qualified	N
Density (Mbit)	256
Initial Access Time (ns)	NA
Interface Frequency (SDR / DDR) (MHz)	133 / 66
Max. Operating Voltage (V)	3.60
Min. Operating Voltage (V)	2.70
Operating Voltage (V)	3
Part Family	Serial NOR
Series	FL-L
Tape & Reel	N
Temperature Range (Min C to Max C)	-55C to +125C

### DESIGN SUPPORT

- [Development Kits](#)
- [Forums](#)
- [Knowledge Base](#)
- [Packaging](#)
- [Product Brochures](#)
- [Quality & Reliability](#)
- [Samples](#)
- [Technical Support](#)
- [Technical Training](#)
- [Third Party Network \(CYPros\)](#)

### PRICING & INVENTORY AVAILABILITY

1-9 unit Price*	10-24 unit Price*	25-99 unit Price*	100-249 unit Price*	250-999 unit Price*	1000+ unit Price*
Contact Sales					

Availability	Quantity	Ships In	Buy from Cypress	Buy from Distributors
Out of Stock	0	<a href="#">Please click here to check lead times</a>	Contact Sales	Contact Sales

\* Prices are shown in United States dollars and are for budgetary use only for volume of 1ku

### TRAINING

- [Workshops](#)
- [Training On-Demand](#)
- [Webinars](#)

### PACKAGING/ORDERING

No. of Pins	36
Package Cross Section Drawing	<a href="#">Download</a>
Package Carrier	TUBE
Package Carrier Drawing / Orientation	<a href="#">Package Orientation</a>
Minimum Order Quantity (MOQ)	5
Order Increment	5
Estimated Lead Time (days)	182
HTS Code	8542.32.0051
ECCN Suball	3A001.A.2.C

### QUALITY AND ROHS

Moisture Sensitivity Level (MSL)	1
Peak Reflow Temp. (°C)	220 (Cypress Reflow Profile)
RoHS Compliant	Y Print RoHS Certificate of Compliance
PB Free	Y
Lead/Ball Finish	Au, Ni/Au
Marking	Cypress Marking Format

### TECHNICAL DOCUMENTS

#### Application Notes (28)

- [AN98551 - Advanced Sector Protection \(ASP\) in Cypress Quad SPI, Octal SPI, and HyperFlash Device Families Nov 11, 2019](#)
- [AN202471 - Migrating to Cypress S25FL-L Serial NOR Flash from Winbond W25Q-JV/FV, Micron N25Q-A, and Macronix M25L-F Devices Mar 19, 2019](#)
- [AN217010 - Migrating from S25FL1-K Serial NOR Flash to S25FL064L Serial NOR Flash Jul 20, 2018](#)
- [AN216999 - Migrating from S25FL064P Serial NOR Flash Products to S25FL064L Serial NOR Flash Products May 29, 2018](#)
- [Show More](#)

#### SOLUTIONS

- [Automotive](#)
- [Industrial](#)
- [Consumer](#)

#### PRODUCTS

- [Wireless](#)
- [Microcontrollers \(MCUs\)](#)
- [Memory](#)
- [Universal Serial Bus \(USB\)](#)
- [Power Management](#)
- [Touch Sensing](#)
- [Clocks & Buffers](#)

#### DESIGN SUPPORT

- [Community](#)
- [Videos](#)
- [Quality & Reliability](#)
- [Product Roadmaps](#)

#### ABOUT US

- [Investors](#)
- [Careers](#)

#### CORPORATE HEADQUARTERS

Cypress Semiconductor Corp.  
198 Champion Court  
San Jose, CA 95134 USA  
Tel: +1-408-943-2600

#### CUSTOMER SERVICE SUPPORT

+1-800-541-4736  
Hours:  
8:00AM - 5:00PM (local time)  
[Create a MyCase](#)  
[Cypress Developer Community](#)

#### INTERNATIONAL SUPPORT

+1-408-943-2600  
United States +1-800-541-4736  
Hours:  
4:30AM - 1:30PM (pacific time)  
7:30PM - 4:30AM (standard time)

#### OTHER REQUESTS

- [Contact Us](#)
- [Report a Website Problem](#)
- [Report a Security Vulnerability](#)

