

# PNP Transistor, 100 V, 3.0 A, Low $V_{CE(sat)}$

## NSS1C300ET4G

onsemi's e<sup>2</sup>PowerEdge family of low  $V_{CE(sat)}$  transistors are surface mount devices featuring ultra low saturation voltage ( $V_{CE(sat)}$ ) and high current gain capability. These are designed for use in low voltage, high speed switching applications where affordable efficient energy control is important.

Typical applications are DC-DC converters and power management in portable and battery powered products such as cellular and cordless phones, PDAs, computers, printers, digital cameras and MP3 players. Other applications are low voltage motor controls in mass storage products such as disc drives and tape drives. In the automotive industry they can be used in air bag deployment and in the instrument cluster. The high current gain allows e<sup>2</sup>PowerEdge devices to be driven directly from PMU's control outputs, and the Linear Gain (Beta) makes them ideal components in analog amplifiers.

### Features

- Complement to NSS1C301ET4G
- NSV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable
- These Devices are Pb-Free and are RoHS Compliant



### MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ )

| Rating                                                                                            | Symbol         | Max          | Unit                     |
|---------------------------------------------------------------------------------------------------|----------------|--------------|--------------------------|
| Collector-Base Voltage                                                                            | $V_{CBO}$      | 140          | Vdc                      |
| Collector-Emitter Voltage                                                                         | $V_{CEO}$      | 100          | Vdc                      |
| Emitter-Base Voltage                                                                              | $V_{EB}$       | 6.0          | Vdc                      |
| Collector Current - Continuous                                                                    | $I_C$          | 3.0          | Adc                      |
| Collector Current - Peak                                                                          | $I_{CM}$       | 6.0          | Adc                      |
| Base Current                                                                                      | $I_B$          | 0.5          | Adc                      |
| Total Power Dissipation<br>@ $T_C = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$          | $P_D$          | 33<br>0.26   | W<br>W/ $^\circ\text{C}$ |
| Total Power Dissipation (Note 1)<br>@ $T_A = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$ | $P_D$          | 2.1<br>0.017 | W<br>W/ $^\circ\text{C}$ |
| Operating and Storage Junction<br>Temperature Range                                               | $T_J, T_{stg}$ | -65 to +150  | $^\circ\text{C}$         |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.


1. These ratings are applicable when surface mounted on the minimum pad sizes recommended.

## 100 VOLTS, 3.0 AMPS PNP LOW $V_{CE(sat)}$ TRANSISTOR



**DPAK  
CASE 369C  
STYLE 1**

### MARKING DIAGRAM



Y = Year  
WW = Work Week  
1C30E = Device Code  
G = Pb-Free

### ORDERING INFORMATION

| Device       | Package           | Shipping†            |
|--------------|-------------------|----------------------|
| NSS1C300ET4G | DPAK<br>(Pb-Free) | 2500/<br>Tape & Reel |
| NSV1C300ET4G | DPAK<br>(Pb-Free) | 2500/<br>Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, [BRD8011/D](http://BRD8011/D).

# NSS1C300ET4G

## THERMAL CHARACTERISTICS

| Characteristic                                   | Symbol          | Max  | Unit                 |
|--------------------------------------------------|-----------------|------|----------------------|
| Thermal Resistance, Junction-to-Case             | $R_{\theta JC}$ | 3.8  | $^{\circ}\text{C/W}$ |
| Thermal Resistance, Junction-to-Ambient (Note 2) | $R_{\theta JA}$ | 59.5 | $^{\circ}\text{C/W}$ |

2. These ratings are applicable when surface mounted on the minimum pad sizes recommended.

## ELECTRICAL CHARACTERISTICS ( $T_A = 25^{\circ}\text{C}$ unless otherwise noted)

| Characteristic                                                               | Symbol        | Min  | Typ | Max  | Unit            |
|------------------------------------------------------------------------------|---------------|------|-----|------|-----------------|
| <b>OFF CHARACTERISTICS</b>                                                   |               |      |     |      |                 |
| Collector-Emitter Breakdown Voltage<br>( $I_C = -10\text{ mA}$ , $I_B = 0$ ) | $V_{(BR)CEO}$ | -100 | -   | -    | Vdc             |
| Collector-Base Breakdown Voltage<br>( $I_C = -0.1\text{ mA}$ , $I_E = 0$ )   | $V_{(BR)CBO}$ | -140 | -   | -    | Vdc             |
| Emitter-Base Breakdown Voltage<br>( $I_E = -0.1\text{ mA}$ , $I_C = 0$ )     | $V_{(BR)EBO}$ | -6.0 | -   | -    | Vdc             |
| Collector Cutoff Current<br>( $V_{CB} = -140\text{ Vdc}$ , $I_E = 0$ )       | $I_{CBO}$     | -    | -   | -0.1 | $\mu\text{Adc}$ |
| Emitter Cutoff Current<br>( $V_{EB} = -6.0\text{ Vdc}$ )                     | $I_{EBO}$     | -    | -   | -0.1 | $\mu\text{Adc}$ |

## ON CHARACTERISTICS

|                                                                                                                                                                                                                                                                         |               |                         |                  |                                      |     |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-------------------------|------------------|--------------------------------------|-----|
| DC Current Gain (Note 3)<br>( $I_C = -0.1\text{ A}$ , $V_{CE} = -2.0\text{ V}$ )<br>( $I_C = -0.5\text{ A}$ , $V_{CE} = -2.0\text{ V}$ )<br>( $I_C = -1.0\text{ A}$ , $V_{CE} = -2.0\text{ V}$ )<br>( $I_C = -3.0\text{ A}$ , $V_{CE} = -2.0\text{ V}$ )                | $h_{FE}$      | 180<br>180<br>120<br>50 | -<br>-<br>-<br>- | -<br>-<br>360<br>-                   | -   |
| Collector-Emitter Saturation Voltage (Note 3)<br>( $I_C = -0.1\text{ A}$ , $I_B = -10\text{ mA}$ )<br>( $I_C = -1.0\text{ A}$ , $I_B = -0.100\text{ A}$ )<br>( $I_C = -2.0\text{ A}$ , $I_B = -0.200\text{ A}$ )<br>( $I_C = -3.0\text{ A}$ , $I_B = -0.300\text{ A}$ ) | $V_{CE(sat)}$ | -<br>-<br>-<br>-        | -<br>-<br>-<br>- | -0.070<br>-0.150<br>-0.250<br>-0.400 | V   |
| Base-Emitter Saturation Voltage (Note 3)<br>( $I_C = -1.0\text{ A}$ , $I_B = -0.1\text{ A}$ )                                                                                                                                                                           | $V_{BE(sat)}$ | -                       | -                | -1.0                                 | V   |
| Base-Emitter Turn-on Voltage (Note 3)<br>( $I_C = -1.0\text{ A}$ , $V_{CE} = -2.0\text{ V}$ )                                                                                                                                                                           | $V_{BE(on)}$  | -                       | -                | -0.900                               | V   |
| Cutoff Frequency<br>( $I_C = -500\text{ mA}$ , $V_{CE} = -10\text{ V}$ , $f = 100\text{ MHz}$ )                                                                                                                                                                         | $f_T$         | -                       | 100              | -                                    | MHz |
| Input Capacitance<br>( $V_{EB} = 5.0\text{ V}$ , $f = 1.0\text{ MHz}$ )                                                                                                                                                                                                 | $C_{ibo}$     | -                       | 360              | -                                    | pF  |
| Output Capacitance<br>( $V_{CB} = 10\text{ V}$ , $f = 1.0\text{ MHz}$ )                                                                                                                                                                                                 | $C_{obo}$     | -                       | 60               | -                                    | pF  |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

3. Pulsed Condition: Pulse Width = 300  $\mu\text{s}$ , Duty Cycle  $\leq 2\%$ .

TYPICAL CHARACTERISTICS




Figure 1. DC Current Gain




Figure 2. DC Current Gain




Figure 3. Collector-Emitter Saturation Voltage




Figure 4. Collector-Emitter Saturation Voltage




Figure 5. Base-Emitter Saturation Voltage




Figure 6. Base-Emitter Saturation Voltage

# NSS1C300ET4G

## TYPICAL CHARACTERISTICS




Figure 7. Base-Emitter On Voltage




Figure 8. Collector Saturation Region




Figure 9. Capacitance




Figure 10. Current-Gain-Bandwidth Product




Figure 11. Safe Operating Area

TYPICAL CHARACTERISTICS





Figure 12. Typical Transient Thermal Response, Junction-to-Case



# MECHANICAL CASE OUTLINE PACKAGE DIMENSIONS



SCALE 1:1

## DPAK (SINGLE GAUGE) CASE 369C ISSUE F

DATE 21 JUL 2015




### NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: INCHES.
3. THERMAL PAD CONTOUR OPTIONAL WITHIN DIMENSIONS b3, L3 and Z.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.006 INCHES PER SIDE.
5. DIMENSIONS D AND E ARE DETERMINED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY.
6. DATUMS A AND B ARE DETERMINED AT DATUM PLANE H.
7. OPTIONAL MOLD FEATURE.

| DIM | INCHES |       | MILLIMETERS |       |
|-----|--------|-------|-------------|-------|
|     | MIN    | MAX   | MIN         | MAX   |
| A   | 0.086  | 0.094 | 2.18        | 2.38  |
| A1  | 0.000  | 0.005 | 0.00        | 0.13  |
| b   | 0.025  | 0.035 | 0.63        | 0.89  |
| b2  | 0.028  | 0.045 | 0.72        | 1.14  |
| b3  | 0.180  | 0.215 | 4.57        | 5.46  |
| c   | 0.018  | 0.024 | 0.46        | 0.61  |
| c2  | 0.018  | 0.024 | 0.46        | 0.61  |
| D   | 0.235  | 0.245 | 5.97        | 6.22  |
| E   | 0.250  | 0.265 | 6.35        | 6.73  |
| e   | 0.090  | BSC   | 2.29        | BSC   |
| H   | 0.370  | 0.410 | 9.40        | 10.41 |
| L   | 0.055  | 0.070 | 1.40        | 1.78  |
| L1  | 0.114  | REF   | 2.90        | REF   |
| L2  | 0.020  | BSC   | 0.51        | BSC   |
| L3  | 0.035  | 0.050 | 0.89        | 1.27  |
| L4  | ---    | 0.040 | ---         | 1.01  |
| Z   | 0.155  | ---   | 3.93        | ---   |

## GENERIC MARKING DIAGRAM\*



IC


Discrete

XXXXXX = Device Code  
A = Assembly Location  
L = Wafer Lot  
Y = Year  
WW = Work Week  
G = Pb-Free Package

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "•", may or may not be present. Some products may not follow the Generic Marking.

- STYLE 1:  
PIN 1. BASE  
2. COLLECTOR  
3. EMITTER  
4. COLLECTOR
- STYLE 2:  
PIN 1. GATE  
2. DRAIN  
3. SOURCE  
4. DRAIN
- STYLE 3:  
PIN 1. ANODE  
2. CATHODE  
3. ANODE  
4. CATHODE
- STYLE 4:  
PIN 1. CATHODE  
2. ANODE  
3. GATE  
4. ANODE
- STYLE 5:  
PIN 1. GATE  
2. ANODE  
3. CATHODE  
4. ANODE
- STYLE 6:  
PIN 1. MT1  
2. MT2  
3. GATE  
4. MT2
- STYLE 7:  
PIN 1. GATE  
2. COLLECTOR  
3. EMITTER  
4. COLLECTOR
- STYLE 8:  
PIN 1. N/C  
2. CATHODE  
3. ANODE  
4. CATHODE
- STYLE 9:  
PIN 1. ANODE  
2. CATHODE  
3. RESISTOR ADJUST  
4. CATHODE
- STYLE 10:  
PIN 1. CATHODE  
2. ANODE  
3. CATHODE  
4. ANODE

## SOLDERING FOOTPRINT\*



SCALE 3:1 (mm inches)

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

|                  |                     |                                                                                                                                                                                  |
|------------------|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOCUMENT NUMBER: | 98AON10527D         | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION:     | DPAK (SINGLE GAUGE) | PAGE 1 OF 1                                                                                                                                                                      |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Email Requests to: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**onsemi Website:** [www.onsemi.com](http://www.onsemi.com)

### TECHNICAL SUPPORT

**North American Technical Support:**

Voice Mail: 1 800-282-9855 Toll Free USA/Canada

Phone: 011 421 33 790 2910

**Europe, Middle East and Africa Technical Support:**

Phone: 00421 33 790 2910

For additional information, please contact your local Sales Representative

