




Wet Tantalum HI-TMP[®] Capacitors Tantalum Case With Glass-to-Tantalum Hermetic Seal for -55 °C to +200 °C Operation



LINKS TO ADDITIONAL RESOURCES



PERFORMANCE CHARACTERISTICS

Operating Temperature: -55 °C to +85 °C
(to +200 °C with voltage derating)

Capacitance Tolerance: at 120 Hz, +25 °C; $\pm 20\%$ standard; $\pm 10\%$

DC Leakage Current (DCL Max.): at +25 °C and above: leakage current shall not exceed the values listed in the Standard Ratings tables.

Life Test: capacitors are capable of withstanding a minimum 500 h life test at a temperature of +200 °C at the applicable derated DC working voltage.

FEATURES

- High capacitance
- Hermetically sealed, tantalum case
- +200 °C high temperature
- Terminations: axial, standard tin / lead (SnPb)
- 100 % tin (RoHS-compliant) available
- Mounting: through-hole
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912



RoHS*
Available

**HALOGEN
FREE
GREEN
(5-2008)**
Available

Note

* This datasheet provides information about parts that are RoHS-compliant and / or parts that are non RoHS-compliant. For example, parts with lead (Pb) terminations are not RoHS-compliant. Please see the information / tables in this datasheet for details

APPLICATIONS

- Industrial
- Petroleum exploration
- High temperature / high stress environment

ORDERING INFORMATION

| 134D | 227 | X0 | 100 | K | 6 | E3 |
|------|---|------------------------------------|---|----------------------------------|--|--|
| TYPE | CAPACITANCE | CAPACITANCE TOLERANCE | DC VOLTAGE RATING AT +85 °C | CASE CODE | CASE INSULATION | RoHS-COMPLIANT |
| | This is expressed in picofarads. The first two digits are the significant figures. The third is the number of zeros to follow | X0 = $\pm 20\%$ X9 = $\pm 10\%$ | This is expressed in volts. To complete the three-digit block, zeros precede the voltage rating. A decimal point is indicated by an "R" (6R3 = 6.3 V) | See Ratings and Case Codes table | 8 = no outer case insulation 6 = high temperature insulation film | E3 = 100 % tin termination (RoHS-compliant design) Blank = SnPb termination (standard design) |

Note

- Packaging: the use of formed plastic trays for packaging these axial lead components is standard. Tape and reel is not available due to the unit weight



| DIMENSIONS in inches [millimeters] | | | | | | |
|---|--------------------|--------------------------------|--|-----------------------|---------------------------------|-------------------|
| <p>0.0253 ± 0.002 [0.64 ± 0.05] dia. (No. 22 AWG tinned nickel leads solderable and weldable)</p> | | | | | | |
| CASE CODE | | D | L ₁ (1) | L ₂ (Max.) | E | WEIGHT (g) (Max.) |
| TYPE 134D | CLR 79 / 81 EQUIV. | | | | | |
| C | T1 | 0.188 ± 0.016 [4.78 ± 0.41] | 0.453 + 0.031 / - 0.016 [11.51 + 0.79 / - 0.41] | 0.734 [18.64] | 1.500 ± 0.250 [38.10 ± 6.35] | 2.6 |
| F | T2 | 0.281 ± 0.016 [7.14 ± 0.41] | 0.641 + 0.031 / - 0.016 [16.28 + 0.79 / - 0.41] | 0.922 [23.42] | 2.250 ± 0.250 [57.15 ± 6.35] | 6.2 |
| T | T3 | 0.375 ± 0.016 [9.53 ± 0.41] | 0.766 + 0.031 / - 0.016 [19.46 + 0.79 / - 0.41] | 1.047 [26.59] | 2.250 ± 0.250 [57.15 ± 6.35] | 11.6 |
| K | T4 | 0.375 ± 0.016 [9.53 ± 0.41] | 1.062 + 0.031 / - 0.016 [26.97 + 0.79 / - 0.41] | 1.343 [34.11] | 2.250 ± 0.250 [57.15 ± 6.35] | 17.7 |

Note

(1) For insulated parts, add 0.015 inches [0.38 mm] to the diameter. The insulation shall lap over the ends of the capacitor body

| STANDARD RATINGS | | | | | | | | | | | | |
|--|----------------|---------------------|---------------|----------------|--------|----------------------------|--------------------------|----------------|--------|---------------------------------|----------------------|--------------------------------------|
| CAPACITANCE AT 25 °C 120 Hz (µF) | MAX. CASE CODE | MAX. 120 Hz ESR (Ω) | MAX. DCL (µA) | | | MAX. IMP., Z AT -25 °C (Ω) | MAX. ΔCAP. AT -25 °C (%) | TYP. ΔCAP. (%) | | AC RIPPLE 85 °C 40 kHz (mA) RMS | PART NUMBER | LIFE TEST PERFORMANCE (h AT +200 °C) |
| | | | 25 °C | 85 °C / 125 °C | 200 °C | | | 85 °C | 125 °C | | | |
| 50 V_{DC} AT 85 °C; 30 V_{DC} AT 125 °C; 30 V_{DC} AT 200 °C | | | | | | | | | | | | |
| 68 | C | 1.50 | 1 | 5 | 50 | 22 | -6 | 12 | 55 | 1400 | 134D686(1)050C(2)(3) | 500 |
| 220 | F | 0.90 | 2 | 10 | 100 | 9 | -15 | 13 | 50 | 2300 | 134D227(1)050F(2)(3) | 500 |
| 470 | T | 0.75 | 3 | 25 | 250 | 6 | -24 | 10 | 25 | 2650 | 134D477(1)050T(2)(3) | 500 |
| 680 | K | 0.70 | 5 | 40 | 400 | 4 | -22 | 12 | 40 | 2900 | 134D687(1)050K(2)(3) | 500 |
| 60 V_{DC} AT 85 °C; 40 V_{DC} AT 125 °C; 36 V_{DC} AT 200 °C | | | | | | | | | | | | |
| 47 | C | 2.00 | 1 | 5 | 50 | 34 | -8 | 8 | 12 | 1250 | 134D476(1)060C(2)(3) | 500 |
| 150 | F | 1.10 | 2 | 10 | 100 | 13 | -11 | 10 | 30 | 2050 | 134D157(1)060F(2)(3) | 500 |
| 390 | T | 0.90 | 3 | 25 | 250 | 7 | -27 | 10 | 25 | 2450 | 134D397(1)060T(2)(3) | 500 |
| 560 | K | 0.80 | 5 | 40 | 400 | 5 | -21 | 12 | 40 | 2700 | 134D567(1)060K(2)(3) | 500 |
| 75 V_{DC} AT 85 °C; 50 V_{DC} AT 125 °C; 45 V_{DC} AT 200 °C | | | | | | | | | | | | |
| 33 | C | 2.50 | 1 | 5 | 50 | 45 | -3.5 | 8 | 25 | 1100 | 134D336(1)075C(2)(3) | 500 |
| 110 | F | 1.30 | 2 | 10 | 100 | 16 | -8 | 8 | 30 | 1900 | 134D117(1)075F(2)(3) | 500 |
| 330 | T | 1.00 | 3 | 30 | 300 | 8 | -30 | 10 | 25 | 2300 | 134D337(1)075T(2)(3) | 500 |
| 470 | K | 0.90 | 5 | 50 | 500 | 6 | -20 | 10 | 40 | 2550 | 134D477(1)075K(2)(3) | 500 |
| 100 V_{DC} AT 85 °C; 65 V_{DC} AT 125 °C; 60 V_{DC} AT 200 °C | | | | | | | | | | | | |
| 15 | C | 3.50 | 1 | 5 | 50 | 95 | -2.5 | 8 | 25 | 950 | 134D156(1)100C(2)(3) | 500 |
| 68 | F | 2.10 | 2 | 10 | 100 | 25 | -6 | 8 | 25 | 1500 | 134D686(1)100F(2)(3) | 500 |
| 150 | T | 1.60 | 3 | 25 | 250 | 14 | -12 | 8 | 22 | 1800 | 134D157(1)100T(2)(3) | 500 |
| 220 | K | 1.20 | 5 | 50 | 500 | 13 | -44 | 8 | 15 | 2200 | 134D227(1)100K(2)(3) | 1000 |
| 125 V_{DC} AT 85 °C; 85 V_{DC} AT 125 °C; 75 V_{DC} AT 200 °C | | | | | | | | | | | | |
| 10 | C | 5.50 | 1 | 5 | 50 | 145 | -2.5 | 8 | 20 | 750 | 134D106(1)125C(2)(3) | 500 |
| 47 | F | 2.30 | 2 | 10 | 100 | 35 | -5 | 7 | 20 | 1450 | 134D476(1)125F(2)(3) | 500 |
| 50 | F | 2.30 | 3 | 10 | 100 | 35 | -5 | 7 | 20 | 1450 | 134D506(1)125F(2)(3) | 500 |
| 100 | T | 1.80 | 3 | 25 | 250 | 24 | -20 | 8 | 20 | 1700 | 134D107(1)125T(2)(3) | 500 |
| 150 | K | 1.60 | 5 | 50 | 500 | 13 | -10 | 6 | 12 | 1900 | 134D157(1)125K(2)(3) | 500 |

Note

- Part number definitions:
 - Capacitance tolerance: X9 = 10 %, X0 = 20 %
 - Style number: 8 = no film insulation, 6 = high temperature film insulation
 - Termination: blank = standard tin/lead, E3 = RoHS-compliant 100 % tin



| EXTENDED RATINGS | | | | | | | | | | | | |
|--|----------------------|---------------------------|---------------|-------------------|--------|-------------------------------------|-----------------------------------|-------------------|--------|---|----------------------|--|
| CAPACITANCE AT 25 °C 120 Hz (μF) | MAX. CASE CODE | MAX. 120 Hz ESR (Ω) | MAX. DCL (μA) | | | MAX. IMP., Z AT -25 °C (Ω) | MAX. ΔCAP. AT -25 °C (%) | TYP. ΔCAP. (%) | | AC RIPPLE 85 °C 40 kHz (mA) RMS | PART NUMBER | LIFE TEST PERFORMANCE (h AT +200 °C) |
| | | | 25 °C | 85 °C / 125 °C | 200 °C | | | 85 °C | 125 °C | | | |
| 50 V_{DC} AT 85 °C; 30 V_{DC} AT 125 °C; 30 V_{DC} AT 200 °C | | | | | | | | | | | | |
| | C | | | | | | | | | | | |
| | F | | | | | | | | | | | |
| | T | | | | | | | | | | | |
| | K | | | | | | | | | | | |
| 60 V_{DC} AT 85 °C; 40 V_{DC} AT 125 °C; 36 V_{DC} AT 200 °C | | | | | | | | | | | | |
| | C | | | | | | | | | | | |
| | F | | | | | | | | | | | |
| | T | | | | | | | | | | | |
| 1000 | K | 0.50 | 20 | 120 | 1200 | 3 | -25 | < 12 | < 15 | 3500 | 134D108(1)060K(2)(3) | 500 |
| 75 V_{DC} AT 85 °C; 50 V_{DC} AT 125 °C; 45 V_{DC} AT 200 °C | | | | | | | | | | | | |
| | C | | | | | | | | | | | |
| 180 | F | 1.50 | 5 | 25 | | | | 15 | 20 | 2000 | 134D187(1)075F(2)(3) | 500 |
| | T | | | | | | | | | | | |
| 750 | K | 0.60 | 20 | 120 | | 3 | -25 | < 10 | < 15 | 3500 | 134D757(1)075K(2)(3) | 500 |
| 1000 | K | 0.50 | 25 | 90 | | 3 | -30 | < 20 | < 25 | 3500 | 134D108(1)075K(2)(3) | 500 |
| 100 V_{DC} AT 85 °C; 65 V_{DC} AT 125 °C; 60 V_{DC} AT 200 °C | | | | | | | | | | | | |
| | C | | | | | | | | | | | |
| | F | | | | | | | | | | | |
| 220 | T | 1.60 | 5 | 30 | 300 | 15 | -40 | 10 | 15 | 1800 | 134D227(1)100T(2)(3) | 500 |
| 400 | K | 0.70 | 10 | 120 | 1200 | 5 | -15 | 10 | 15 | 3250 | 134D407(1)100K(2)(3) | 500 |
| 470 | K | 0.70 | 25 | 200 | 2000 | 8 | -15 | 5 | 10 | 3250 | 134D477(1)100K(2)(3) | 1000 |
| 560 | K | 0.70 | 25 | 200 | 2000 | 5 | -25 | 15 | 20 | 5500 | 134D567(1)100K(2)(3) | 1000 |
| 750 | K ⁽¹⁾ | 0.90 | 30 | 150 | 1500 | 4 | -30 | 20 | 25 | 4500 | 134D757(1)100K(2)(3) | 500 |
| 125 V_{DC} AT 85 °C; 85 V_{DC} AT 125 °C; 75 V_{DC} AT 200 °C | | | | | | | | | | | | |
| | C | | | | | | | | | | | |
| | F | | | | | | | | | | | |
| | T | | | | | | | | | | | |
| 240 | K | 0.80 | 10 | 50 | 500 | 10 | -10 | 6 | 12 | 2500 | 134D247(1)125K(2)(3) | 500 |
| 350 | K | 0.80 | 25 | 250 | 2500 | 15 | -55 | 8 | 12 | 3250 | 134D357(1)125K(2)(3) | 1000 ⁽²⁾ |

Notes

- In bold and italic: preliminary rating and electrical values. Contact marketing for availability
- Part number definitions:
 - (1) Capacitance tolerance: X9 = 10 %, X0 = 20 %
 - (2) Style number: 8 = no film insulation, 6 = high temperature film insulation
 - (3) Termination: blank = standard tin / lead, E3 = RoHS compliant 100 % tin
- (1) Requires export license for shipments outside the US. Contact marketing for availability
- (2) This rating withstands 62 V_{DC} at 200 °C for 1000 h

| RIPPLE CURRENT MULTIPLIERS VS. FREQUENCY, TEMPERATURE, AND APPLIED PEAK VOLTAGE | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|--------|------|------|------|--------|------|------|------|-------|------|------|------|--------|------|------|------|--------|------|------|------|---------|------|------|------|---|
| FREQUENCY OF APPLIED RIPPLE CURRENT | 120 Hz | | | | 800 Hz | | | | 1 kHz | | | | 10 kHz | | | | 40 kHz | | | | 100 kHz | | | | |
| | ≤ 55 | 85 | 105 | 125 | ≤ 55 | 85 | 105 | 125 | ≤ 55 | 85 | 105 | 125 | ≤ 55 | 85 | 105 | 125 | ≤ 55 | 85 | 105 | 125 | ≤ 55 | 85 | 105 | 125 | |
| % of 85 °C rated peak voltage | 100 % | 0.60 | 0.39 | - | 0.71 | 0.43 | - | - | 0.72 | 0.46 | - | - | 0.88 | 0.55 | - | - | 1.0 | 0.63 | - | - | 1.1 | 0.69 | - | - | |
| | 90 % | 0.60 | 0.46 | - | 0.71 | 0.55 | - | - | 0.72 | 0.55 | - | - | 0.88 | 0.67 | - | - | 1.0 | 0.77 | - | - | 1.1 | 0.85 | - | - | |
| | 80 % | 0.60 | 0.52 | 0.35 | - | 0.71 | 0.62 | 0.42 | - | 0.72 | 0.62 | 0.42 | - | 0.88 | 0.76 | 0.52 | - | 1.0 | 0.87 | 0.59 | - | 1.1 | 0.96 | 0.65 | - |
| | 70 % | 0.60 | 0.58 | 0.44 | - | 0.71 | 0.69 | 0.52 | - | 0.72 | 0.70 | 0.52 | - | 0.88 | 0.85 | 0.64 | - | 1.0 | 0.97 | 0.73 | - | 1.1 | 1.07 | 0.80 | - |
| 66 2/3 % | 0.60 | 0.60 | 0.46 | 0.27 | 0.71 | 0.71 | 0.55 | 0.32 | 0.72 | 0.72 | 0.55 | 0.32 | 0.88 | 0.88 | 0.68 | 0.40 | 1.0 | 1.0 | 0.77 | 0.45 | 1.1 | 1.1 | 0.85 | 0.50 | |



TYPICAL PERFORMANCE CHARACTERISTICS OF 134D CAPACITORS

| ELECTRICAL CHARACTERISTICS | |
|---------------------------------|--|
| ITEM | PERFORMANCE CHARACTERISTICS |
| Operating temperature range | -55 °C to +85 °C (to +200 °C with voltage derating) |
| Capacitor tolerance | ± 20 %, ± 10 % at 120 Hz, at +25 °C |
| Capacitor change by temperature | Limit per Standard Ratings table |
| ESR | Limit per Standard Ratings table, at +25 °C, 120 Hz |
| Impedance | Limit per Standard Ratings table, at -55 °C, 120 Hz |
| DCL (leakage current) | Limit per Standard Ratings table |
| AC ripple current | Limit per Standard Ratings table, at +85 °C and 40 kHz |
| Reverse voltage | None |
| Surge voltage | Surge voltage shall be in accordance with MIL-PRF-39006 and Table 2 of DSCC93026. The DC rated surge voltage is the maximum voltage to which the capacitors can be subjected under any conditions including transients and peak ripple at the highest line voltage. The DC surge voltage is 115 % of rated DC voltage. |

| PERFORMANCE CHARACTERISTICS | |
|-----------------------------|--|
| ITEM | PERFORMANCE CHARACTERISTICS |
| Life testing | Capacitors shall be capable of withstanding a minimum 500 h life test at a temperature +200 °C at derated voltage. |

| ENVIRONMENTAL CHARACTERISTICS | | |
|-------------------------------|--------------------------------------|---|
| ITEM | CONDITION | COMMENTS |
| Seal | MIL-PRF-39006 | When the capacitors are tested as specified in MIL-PRF-39006, there shall be no evidence of leakage. |
| Moisture resistance | MIL-PRF-39006 | Moisture resistance shall be in accordance with MIL-PRF-39006. Number of cycles: 10 continuous cycles |
| Barometric pressure (reduced) | MIL-STD-202, method 105, condition E | Altitude 150 000 feet |

| MECHANICAL CHARACTERISTICS | | |
|----------------------------|--|--|
| ITEM | CONDITION | COMMENTS |
| Shock (specified pulse) | MIL-STD-202, method 213, condition I (100 g) | The capacitors shall meet the requirements of MIL-PRF-39006. |
| Vibration, high frequency | MIL-STD-202, method 204, condition D (20 g peak) | The capacitors shall meet the requirements of MIL-PRF-39006. |
| Thermal shock | MIL-STD-202, method 107, condition A | Thermal shock shall be in accordance with MIL-PRF-39006 when tested for 30 cycles. |
| Solderability | MIL-STD-202, method 208, ANSI/J-STD-002, test A | Solderability shall be in accordance with MIL-PRF-39006. |
| Terminal strength | MIL-STD-202, method 211 | Terminal strength shall be in accordance with MIL-PRF-39006. |
| Resistance to solder heat | MIL-STD-202, method 210, condition C | The capacitors shall meet the requirements of MIL-PRF-39006. |
| Terminals | MIL-STD-1276 | Terminals shall be as specified in MIL-STD-1276. The length and diameter of the terminals shall be as specified in Dimensions table. All terminals shall be permanently secured internally and externally, as applicable. All external joints shall be welded. |
| Marking | MIL-STD-1285 | Marking of capacitors conforms to method I of MIL-STD-1285 and include capacitance (in µF), capacitance tolerance letter, rated voltage, date code, lot symbol, and Vishay trademark. |

| SELECTOR GUIDES | |
|----------------------------|--|
| Tantalum Selector Guide | www.vishay.com/doc?49054 |
| Parameter Comparison Guide | www.vishay.com/doc?42088 |



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.