**ON Semiconductor** 

Is Now

# Onsemi

To learn more about onsemi<sup>™</sup>, please visit our website at <u>www.onsemi.com</u>

onsemi and ONSEMI: and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "onsemi" or its affiliates and/or subsidiaries in the United States and/or other countries. onsemi owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of onsemi product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. onsemi reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and onsemi makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using onsemi products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by onsemi. "Typical" parameters which may be provided in onsemi data sheets and/or or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application is provided for uses as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use onsemi roducts for any such unintended or unauthorized application, Buyer shall indemnify and hold onsemi and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs



Is Now Part of



## **ON Semiconductor**®

## To learn more about ON Semiconductor, please visit our website at <u>www.onsemi.com</u>

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (\_), the underscore (\_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (\_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at <a href="https://www.onsemi.com">www.onsemi.com</a>. Please email any questions regarding the system integration to <a href="https://www.onsemi.com">Fairchild\_questions@onsemi.com</a>.

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or unavteries, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is and its officers, employees, subsidiaries, and filiates, and distributors harmless against all claims, costs, damages,



FAIRCHILD

#### Features


- Stealth Recovery  $t_{rr}$  = 28 ns (@ IF = 8 A)
- Max Forward Voltage, VF = 2.4 V (@ TC = 25°C)
- 600 V Reverse Voltage and High Reliability
- Avalanche Energy Rated
- RoHS Compliant

#### Applications

- SMPS FWD
- · Hard Switched PFC Boost Diode
- UPS Free Wheeling Diode
- Motor Drive FWD
- Snubber Diode

### Description

The ISL9R860P2, ISL9R860S3ST is a STEALTH<sup>TM</sup> diode optimized for low loss performance in high frequency hard switched applications. The STEALTH<sup>TM</sup> family exhibits low reverse recovery current (I<sub>RR</sub>) and exceptionally soft recovery under typical operating conditions. This device is intended for use as a free wheeling or boost diode in power supplies and other power switching applications. The low I<sub>RR</sub> and short ta phase reduce loss in switching transistors. The soft recovery minimizes ringing, expanding the range of conditions under which the diode may be operated without the use of additional snubber circuitry. Consider using the STEALTH<sup>TM</sup> diode with an SMPS IGBT to provide the most efficient and highest power density design at lower cost.



#### Device Maximum Ratings T<sub>c</sub>= 25°C unless otherwise noted


Symbol	Parameter	Ratings	Unit
V <sub>RRM</sub>	Peak Repetitive Reverse Voltage	600	V
V <sub>RWM</sub>	Working Peak Reverse Voltage	600	V
V <sub>R</sub>	DC Blocking Voltage	600	V
I <sub>F(AV)</sub>	Average Rectified Forward Current (T <sub>C</sub> = 147 <sup>o</sup> C)	8	Α
I <sub>FRM</sub>	Repetitive Peak Surge Current (20kHz Square Wave)	16	А
I <sub>FSM</sub>	Nonrepetitive Peak Surge Current (Halfwave 1 Phase 60Hz)	100	Α
PD	Power Dissipation	85	W
E <sub>AVL</sub>	Avalanche Energy (1 A, 40 mH)	20	m
J, T <sub>STG</sub>	Operating and Storage Temperature Range	-55 to 175	°C
T <sub>L</sub> T <sub>PKG</sub>	Maximum Temperature for Soldering Leads at 0.063in (1.6mm) from Case for 10s Package Body for 10s, See Techbrief TB334	300 260	℃ ℃

©2001 Fairchild Semiconductor Corporation ISL9R860P2, ISL9R860S3ST Rev. 2

August 2018


	ber Top Mark	Package	Packing M	ethod	Reel Size	Tape Width		th (	Quantity	
	SL9R860P2 R860P2 TO-220AC-2L		Tube N/A		N/A	N/A			50	
SL9R860S3ST R860S3S TO-263AB(D <sup>2</sup> -PAK		Reel 13" Dia		13" Dia	24mm			800		
Electric	al Characteri	· ·	,	notod						
Symbol	Parar	-		Conditions		Min	Тур	Мах	Unit	
			1031 0	Jonations		IVIIII	тур	IVIAN	Offic	
	Characteristics					-	100	<u> </u>		
I <sub>R</sub>	Instantaneous Reverse Current		V <sub>R</sub> = 600 V	T <sub>C</sub> =		-	-	100	μA	
				1 <sub>C</sub> =	125°C	-	-	1.0	mA	
On State	Characteristics									
V <sub>F</sub>	Instantaneous Forward Voltage		I <sub>F</sub> = 8 A T <sub>0</sub>	T <sub>C</sub> =	25°C	-	2.0	2.4	V	
		-			125°C	-	1.6	2.0	V	
Dynamic	Characteristics									
CJ	Junction Capacitanc		V <sub>R</sub> = 10 V, I <sub>F</sub> = 0	Δ		-	30	-	pF	
CJ	Sunction Capacitanc	6	$v_{\rm R} = 10 v_{\rm r} i_{\rm F} = 0$			-	50	-	р	
Switching	g Characteristic	s								
t <sub>rr</sub>	Reverse Recovery T	ïme	$I_F = 1 \text{ A}, \text{ di}_F/\text{dt} =$	100 A/μs	, V <sub>R</sub> = 30 V	-	18	25	ns	
			$I_F = 8 A, di_F/dt =$	100 A/μs	, V <sub>R</sub> = 30 V	-	21	30	ns	
	Reverse Recovery T		I <sub>F</sub> = 8 A,			-	28	-	ns	
	Reverse Recovery C		$di_{F}/dt = 200 A/\mu s,$ $V_{R} = 390 V, T_{C} = 25^{\circ}C$ $I_{F} = 8 A,$ $di_{F}/dt = 200 A/\mu s,$ $V_{R} = 390 V,$ $T_{C} = 125^{\circ}C$			-	3.2	-	A	
	Reverse Recovery C	-				-	50	-	nC	
	Reverse Recovery T					-	77	-	ns	
S	Softness Factor (t <sub>b</sub> /t					-	3.7	-		
	Reverse Recovery C				_	-	3.4	-	A	
	Reverse Recovery C					-	150 53	-	nC	
	Softness Factor (t <sub>b</sub> /t			I <sub>F</sub> = 8 A, di <sub>F</sub> /dt = 600 A/μs,		-	2.5	-	ns	
	Reverse Recovery C		V <sub>R</sub> = 390 V,			-	6.5	-	A	
	Reverse Recovery C		T <sub>C</sub> = 125°C			_	195	-	nC	
	Maximum di/dt durin	-				-	500	-	A/µs	
	Characteristics	0.0								
		hundien to Orea	Γ					4 75	80/14/	
000	Thermal Resistance	Junction to Case	TO 220	_		-	-	62	°C/W °C/W	
R <sub>0JA</sub>		Junction to Ambient				-	-	62	°C/W	
$R_{ extsf{ heta}JA}$	Thermal Resistance		10-203					02	0/11	

2




©2001 Fairchild Semiconductor Corporation ISL9R860P2, ISL9R860S3ST Rev. 2

www.fairchildsemi.com




www.fairchildsemi.com




©2001 Fairchild Semiconductor Corporation ISL9R860P2, ISL9R860S3ST Rev. 2

www.fairchildsemi.com



Downloaded from Arrow.com.



http://www.fairchildsemi.com/package/packageDetails.html?id=PN\_TT263-002.

©2001 Fairchild Semiconductor Corporation ISL9R860P2, ISL9R860S3ST Rev. 2

Downloaded from Arrow.com.

ISL9R860P2, ISL9R860S3ST — STEALTH™ Diode



#### TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

AccuPower™ AX-CAP® BitSiC™ Build it Now™ CorePLUS™ CorePOWER™ CROSSVOLT™ CTL™ Current Transfer Logic™ DEUXPEED® Dual Cool™ EcoSPARK® EfficentMax<sup>™</sup> ESBC<sup>™</sup>

Fairchild® Fairchild Semiconductor® FACT Quiet Series™ FACT® FAST® FastvCore™ FETBench™ **FPS™** 

FRFET® Global Power Resource<sup>SM</sup> GreenBridge™ Green FPS™ Green FPS™ e-Series™ Gmax™ GTO™ IntelliMAX™ **ISOPLANAR™** Marking Small Speakers Sound Louder and Better™ MegaBuck™ MICROCOUPLER™ MicroFET™ MicroPak™ MicroPak2™ MillerDrive™ MotionMax™ mWSaver<sup>®</sup> OptoHiT™ **OPTOLOGIC® OPTOPLANAR**<sup>®</sup>

F-PFS™

( )® PowerTrench® PowerXS™ Programmable Active Droop™ QFET® QS™ Quiet Series™ RapidConfigure™ тм Saving our world, 1mW/W/kW at a time™ SignalWise™ SmartMax™ SMART START Solutions for Your Success™ SPM® STEALTH™

Sync-Lock™ SYSTEM<sup>®\*</sup> GENERAL TinyBoost<sup>®</sup> TinyBuck<sup>®</sup> TinyCalc™ TinyLogic® TIŃYOPTO™ TinyPower™ TinyPWM™ TinyWire™ TranSiC™ TriFault Detect™ TRUECURRENT®\*



UHC® Ultra FRFET™ UniFET™ VCX™ VisualMax™ VoltagePlus™ XS™

\*Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

#### DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

SuperFET<sup>®</sup>

SuperSOT™-3

SuperSOT™-6

SuperSOT™-8

SupreMOS®

SyncFET™

LIFE SUPPORT POLICY FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used here in:

- Life support devices or systems are devices or systems which, (a) are 1. intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
- A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

#### ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.Fairchildsemi.com, under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufactures of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed application, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handing and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address and warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

#### **PRODUCT STATUS DEFINITIONS**

Definition	of Terms
------------	----------

Datasheet Identification	Product Status	Definition
Advance Information	Formative / In Design	Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.
No Identification Needed	Full Production	Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.
Obsolete	Not In Production	Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.
		Rev.

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at <u>www.onsemi.com/site/pdf/Patent-Marking.pdf</u>. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor haves against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death a

#### PUBLICATION ORDERING INFORMATION

#### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor 19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada Email: orderlit@onsemi.com N. American Technical Support: 800–282–9855 Toll Free USA/Canada Europe, Middle East and Africa Technical Support: Phone: 421 33 790 2910 Japan Customer Focus Center Phone: 81–3–5817–1050 ON Semiconductor Website: www.onsemi.com

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

© Semiconductor Components Industries, LLC

Downloaded from Arrow.com.