

128Mb 0-die SDRAM

54TSOP(II) with Lead-Free & Halogen-Free
(RoHS compliant)

datasheet

SAMSUNG ELECTRONICS RESERVES THE RIGHT TO CHANGE PRODUCTS, INFORMATION AND SPECIFICATIONS WITHOUT NOTICE.

Products and specifications discussed herein are for reference purposes only. All information discussed herein is provided on an "AS IS" basis, without warranties of any kind.

This document and all information discussed herein remain the sole and exclusive property of Samsung Electronics. No license of any patent, copyright, mask work, trademark or any other intellectual property right is granted by one party to the other party under this document, by implication, estoppel or otherwise.

Samsung products are not intended for use in life support, critical care, medical, safety equipment, or similar applications where product failure could result in loss of life or personal or physical harm, or any military or defense application, or any governmental procurement to which special terms or provisions may apply.

For updates or additional information about Samsung products, contact your nearest Samsung office.

All brand names, trademarks and registered trademarks belong to their respective owners.

© 2010 Samsung Electronics Co., Ltd. All rights reserved.

Revision History

<u>Revision No.</u>	<u>History</u>	<u>Draft Date</u>	<u>Remark</u>	<u>Editor</u>
1.0	- First Spec. Release	May. 2010	-	S.H.Kim



[Table Of Contents](#)

128Mb 0-die SDRAM

1. KEY FEATURES.....	4
2. GENERAL DESCRIPTION	4
3. ORDERING INFORMATION	4
4. PACKAGE PHYSICAL DIMENSION	5
5. FUNCTIONAL BLOCK DIAGRAM	6
6. PIN CONFIGURATION (TOP VIEW).....	7
7. INPUT/OUTPUT FUNCTION DESCRIPTION	7
8. ABSOLUTE MAXIMUM RATINGS	8
9. DC OPERATING CONDITIONS	8
10. CAPACITANCE	8
11. DC CHARACTERISTICS (x8).....	9
12. DC CHARACTERISTICS (x16).....	10
13. AC OPERATING TEST CONDITIONS	11
14. OPERATING AC PARAMETER	12
15. AC CHARACTERISTICS	13
16. DQ BUFFER OUTPUT DRIVE CHARACTERISTICS.....	13
17. IBIS SPECIFICATION.....	14
18. SIMPLIFIED TRUTH TABLE	18

1. KEY FEATURES

- JEDEC standard 3.3V power supply
- LVTTTL compatible with multiplexed address
- Four banks operation
- MRS cycle with address key programs
 - CAS latency (2 & 3)
 - Burst length (1, 2, 4, 8 & Full page)
 - Burst type (Sequential & Interleave)
- All inputs are sampled at the positive going edge of the system clock.
- Burst read single-bit write operation
- DQM (x8) & L(U)DQM (x16) for masking
- Auto & self refresh
- 64ms refresh period (4K Cycle)
- 54pin TSOP II **Lead-Free and Halogen-Free** package
- **RoHS compliant**

2. GENERAL DESCRIPTION

The K4S280832O / K4S281632O is 134,217,728 bits synchronous high data rate Dynamic RAM organized as 4 x 4,194,304 words by 8 bits / 4 x 2,097,152 words by 16 bits, fabricated with SAMSUNG's high performance CMOS technology. Synchronous design allows precise cycle control with the use of system clock I/O transactions are possible on every clock cycle. Range of operating frequencies, programmable burst length and programmable latencies allow the same device to be useful for a variety of high bandwidth, high performance memory system applications.


3. ORDERING INFORMATION

Part No.	Organization	Max Freq.	Interface	Package
K4S280832O-LC/L75	16Mb x 8	133MHz (CL=3)	LVTTTL	54pin TSOP(II) Lead-Free & Halogen-Free
K4S280832O-LC/L60	16Mb x 8	166MHz (CL=3)		
K4S281632O-LC/L75	8Mb x 16	133MHz (CL=3)		
K4S281632O-LC/L60	8Mb x 16	166MHz (CL=3)		


[Table 1] Row & Column address configuration

Organization	Row Address	Column Address
16Mx8	A0~A11	A0-A9
8Mx16	A0~A11	A0-A8

4. PACKAGE PHYSICAL DIMENSION



5. FUNCTIONAL BLOCK DIAGRAM



* Samsung Electronics reserves the right to change products or specification without notice.

6. PIN CONFIGURATION (TOP VIEW)

x16	x8		x8	x16
V _{DD}	V _{DD}	1	54	V _{SS}
DQ0	DQ0	2	53	DQ7
V _{DDQ}	V _{DDQ}	3	52	V _{SSQ}
DQ1	N.C	4	51	N.C
DQ2	DQ1	5	50	DQ6
V _{SSQ}	V _{SSQ}	6	49	V _{DDQ}
DQ3	N.C	7	48	N.C
DQ4	DQ2	8	47	DQ5
V _{DDQ}	V _{DDQ}	9	46	V _{SSQ}
DQ5	N.C	10	45	N.C
DQ6	DQ3	11	44	DQ4
V _{SSQ}	V _{SSQ}	12	43	V _{DDQ}
DQ7	N.C	13	42	N.C
V _{DD}	V _{DD}	14	41	V _{SS}
LDQM	N.C	15	40	N.C/RFU
WE	WE	16	39	DQM
CAS	CAS	17	38	CLK
RAS	RAS	18	37	CKE
CS	CS	19	36	N.C
BA0	BA0	20	35	A11
BA1	BA1	21	34	A9
A10/AP	A10/AP	22	33	A8
A0	A0	23	32	A7
A1	A1	24	31	A6
A2	A2	25	30	A5
A3	A3	26	29	A4
V _{DD}	V _{DD}	27	28	V _{SS}

54Pin TSOP
(400mil x 875mil)
(0.8 mm Pin pitch)

7. INPUT/OUTPUT FUNCTION DESCRIPTION

Pin	Name	Description
CLK	System clock	Active on the positive going edge to sample all inputs.
$\overline{\text{CS}}$	Chip select	Disables or enables device operation by masking or enabling all inputs except CLK, CKE and DQM
CKE	Clock enable	Masks system clock to freeze operation from the next clock cycle. CKE should be enabled at least one cycle prior to new command. Disable input buffers for power down in standby.
A0 ~ A11	Address	Row/column addresses are multiplexed on the same pins. Row address : RA0 ~ RA11, Column address : (x8 : CA0 ~ CA9), (x16 : CA0 ~ CA8)
BA0 ~ BA1	Bank select address	Selects bank to be activated during row address latch time. Selects bank for read/write during column address latch time.
$\overline{\text{RAS}}$	Row address strobe	Latches row addresses on the positive going edge of the CLK with $\overline{\text{RAS}}$ low. Enables row access & precharge.
$\overline{\text{CAS}}$	Column address strobe	Latches column addresses on the positive going edge of the CLK with $\overline{\text{CAS}}$ low. Enables column access.
$\overline{\text{WE}}$	Write enable	Enables write operation and row precharge. Latches data in starting from CAS, WE active.
DQM	Data input/output mask	Makes data output Hi-Z, tSHZ after the clock and masks the output. Blocks data input when DQM active.
DQ0 ~ N	Data input/output	Data inputs/outputs are multiplexed on the same pins. (x8 : DQ0 ~ 7), (x16 : DQ0 ~ 15)
V _{DD} /V _{SS}	Power supply/ground	Power and ground for the input buffers and the core logic.
V _{DDQ} /V _{SSQ}	Data output power/ground	Isolated power supply and ground for the output buffers to provide improved noise immunity.
N.C/RFU	No connection /reserved for future use	This pin is recommended to be left No Connection on the device.

8. ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
Voltage on any pin relative to V_{SS}	V_{IN}, V_{OUT}	-1.0 ~ 4.6	V
Voltage on V_{DD} supply relative to V_{SS}	V_{DD}, V_{DDQ}	-1.0 ~ 4.6	V
Storage temperature	T_{STG}	-55 ~ +150	°C
Power dissipation	P_D	1	W
Short circuit current	I_{OS}	50	mA

NOTE : Permanent device damage may occur if "ABSOLUTE MAXIMUM RATINGS" are exceeded.
Functional operation should be restricted to recommended operating condition.
Exposure to higher than recommended voltage for extended periods of time could affect device reliability.

9. DC OPERATING CONDITIONS

Recommended operating conditions (Voltage referenced to $V_{SS} = 0V$, $T_A = 0$ to $70^{\circ}C$)

Parameter	Symbol	Min	Typ	Max	Unit	NOTE
Supply voltage	V_{DD}, V_{DDQ}	3.0	3.3	3.6	V	
Input logic high voltage	V_{IH}	2.0	3.0	$V_{DD}+0.3$	V	1
Input logic low voltage	V_{IL}	-0.3	0	0.8	V	2
Output logic high voltage	V_{OH}	2.4	-	-	V	$I_{OH} = -2mA$
Output logic low voltage	V_{OL}	-	-	0.4	V	$I_{OL} = 2mA$
Input leakage current	I_{LI}	-10	-	10	uA	3

NOTE :
1. V_{IH} (max) = 5.6V AC. The overshoot voltage duration is $\leq 3ns$.
2. V_{IL} (min) = -2.0V AC. The undershoot voltage duration is $\leq 3ns$.
3. Any input $0V \leq V_{IN} \leq V_{DDQ}$.
Input leakage currents include Hi-Z output leakage for all bi-directional buffers with Tri-State outputs.

10. CAPACITANCE

($V_{DD} = 3.3V$, $T_A = 23^{\circ}C$, $f = 1MHz$, $V_{REF} = 1.4V \pm 200 mV$)

Pin	Symbol	Min	Max	Unit
Clock	CCLK	2.5	3.5	pF
$\overline{RAS}$, $\overline{CAS}$, $\overline{WE}$, $\overline{CS}$, CKE, DQM	CIN	2.5	3.8	pF
Address	CADD	2.5	3.8	pF
(x8 : DQ0 ~ DQ7), (x16 : DQ0 ~ DQ15)	COUT	4.0	6.0	pF

11. DC CHARACTERISTICS (x8)

(Recommended operating condition unless otherwise noted, TA = 0 to 70°C)

Parameter	Symbol	Test Condition	Version		Unit	NOTE
			60	75		
Operating current (One bank active)	ICC1	Burst length = 1 $t_{RC} \geq t_{RC(min)}$ IO = 0 mA	40	40	mA	1
Precharge standby current in power-down mode	ICC2P	$CKE \leq V_{IL(max)}$, $t_{CC} = 10ns$	2	2	mA	
	ICC2PS	$CKE \& CLK \leq V_{IL(max)}$, $t_{CC} = \infty$	2	2		
Precharge standby current in non power-down mode	ICC2N	$CKE \geq V_{IH(min)}$, $\overline{CS} \geq V_{IH(min)}$, $t_{CC} = 10ns$ Input signals are changed one time during 20ns	15	15	mA	
	ICC2NS	$CKE \geq V_{IH(min)}$, $CLK \leq V_{IL(max)}$, $t_{CC} = \infty$ Input signals are stable	10	10		
Active standby current in power- down mode	ICC3P	$CKE \leq V_{IL(max)}$, $t_{CC} = 10ns$	5	5	mA	
	ICC3PS	$CKE \& CLK \leq V_{IL(max)}$, $t_{CC} = \infty$	5	5		
Active standby current in non power-down mode (One bank active)	ICC3N	$CKE \geq V_{IH(min)}$, $\overline{CS} \geq V_{IH(min)}$, $t_{CC} = 10ns$ Input signals are changed one time during 20ns	25	25	mA	
	ICC3NS	$CKE \geq V_{IH(min)}$, $CLK \leq V_{IL(max)}$, $t_{CC} = \infty$ Input signals are stable	20	20	mA	
Operating current (Burst mode)	ICC4	IO = 0 mA Page burst 4Banks Activated $t_{CCD} = 2CLKs$	60	60	mA	1
Refresh current	ICC5	$t_{RC} \geq t_{RC(min)}$	100	100	mA	2
Self refresh current	ICC6	$CKE \leq 0.2V$	C	2	mA	3
			L	0.8	mA	4

NOTE :

1. Measured with outputs open.
2. Refresh period is 64ms.
3. K4S280832O-LC
4. K4S280832O-LL
5. Unless otherwise noticed, input swing level is CMOS($V_{IH}/V_{IL} = V_{DDQ}/V_{SSQ}$).

12. DC CHARACTERISTICS (x16)

(Recommended operating condition unless otherwise noted, TA = 0 to 70°C)

Parameter	Symbol	Test Condition	Version		Unit	NOTE
			60	75		
Operating current (One bank active)	ICC1	Burst length = 1 $t_{RC} \geq t_{RC(min)}$ IO = 0 mA	40	40	mA	1
Precharge standby current in power-down mode	ICC2P	$CKE \leq V_{IL(max)}$, $t_{CC} = 10ns$	2	2	mA	
	ICC2PS	$CKE \& CLK \leq V_{IL(max)}$, $t_{CC} = \infty$	2	2		
Precharge standby current in non power-down mode	ICC2N	$CKE \geq V_{IH(min)}$, $\overline{CS} \geq V_{IH(min)}$, $t_{CC} = 10ns$ Input signals are changed one time during 20ns	15	15	mA	
	ICC2NS	$CKE \geq V_{IH(min)}$, $CLK \leq V_{IL(max)}$, $t_{CC} = \infty$ Input signals are stable	10	10		
Active standby current in power- down mode	ICC3P	$CKE \leq V_{IL(max)}$, $t_{CC} = 10ns$	5	5	mA	
	ICC3PS	$CKE \& CLK \leq V_{IL(max)}$, $t_{CC} = \infty$	5	5		
Active standby current in non power-down mode (One bank active)	ICC3N	$CKE \geq V_{IH(min)}$, $\overline{CS} \geq V_{IH(min)}$, $t_{CC} = 10ns$ Input signals are changed one time during 20ns	25	25	mA	
	ICC3NS	$CKE \geq V_{IH(min)}$, $CLK \leq V_{IL(max)}$, $t_{CC} = \infty$ Input signals are stable	20	20	mA	
Operating current (Burst mode)	ICC4	IO = 0 mA Page burst 4Banks Activated $t_{CCD} = 2CLKs$	60	60	mA	1
Refresh current	ICC5	$t_{RC} \geq t_{RC(min)}$	100	100	mA	2
Self refresh current	ICC6	$CKE \leq 0.2V$	C	2	mA	3
			L	0.8	mA	4

NOTE :

1. Measured with outputs open.
2. Refresh period is 64ms.
3. K4S281632O-LC
4. K4S281632O-LL
5. Unless otherwise noticed, input swing level is CMOS($V_{IH}/V_{IL} = V_{DDQ}/V_{SSQ}$).

13. AC OPERATING TEST CONDITIONS

 $(V_{DD} = 3.3V \pm 0.3V, T_A = 0 \text{ to } 70^\circ\text{C})$

Parameter	Value	Unit
Input levels (V_{ih}/V_{il})	2.4/0.4	V
Input timing measurement reference level	1.4	V
Input rise and fall time	$t_r/t_f = 1/1$	ns
Output timing measurement reference level	1.4	V
Output load condition	See Figure 3	




Figure 2. DC output load circuit




Figure 3. AC output load circuit

14. OPERATING AC PARAMETER

(AC operating conditions unless otherwise noted)

Parameter	Symbol	Version		Unit
		60	75	
Row active to row active delay	tRRD(min)	12	15	ns
RAS to CAS delay	tRCD(min)	18	20	ns
Row precharge time	tRP(min)	18	20	ns
Row active time	tRAS(min)	42	45	ns
	tRAS(max)	100		us
Row cycle time	tRC(min)	60	65	ns
Last data in to row precharge	tRDL(min)	2		CLK
Last data in to Active delay	tDAL(min)	2 CLK + tRP		-
Last data in to new col. address delay	tCDL(min)	1		CLK
Last data in to burst stop	tBDL(min)	1		CLK
Col. address to col. address delay	tCCD(min)	1		CLK
Number of valid output data	CAS latency=3	2		ea
	CAS latency=2	-	1	

NOTE : 1. The minimum number of clock cycles is determined by dividing the minimum time required with clock cycle time and then rounding off to the next higher integer.

2. Minimum delay is required to complete write.

3. All parts allow every cycle column address change.

4. In case of row precharge interrupt, auto precharge and read burst stop.

5. In 100MHz and below 100MHz operating conditions, tRDL=1CLK and tDAL=1CLK + 20ns is also supported. SAMSUNG recommends tRDL=2CLK and tDAL=2CLK + tRP.

6. $t_{RC} = t_{RFC}$, $t_{RDL} = t_{WR}$

15. AC CHARACTERISTICS

(AC operating conditions unless otherwise noted)

Parameter		Symbol	60		75	
			Min	Max	Min	Max
CLK cycle time	CAS latency=3	tCC	6	1000	7.5	1000
	CAS latency=2		-		10	
CLK to valid output delay	CAS latency=3	tSAC		5		5.4
	CAS latency=2			-		6
Output data hold time	CAS latency=3	tOH	2.5		3	
	CAS latency=2		-		3	
CLK high pulse width		tCH	2.5		2.5	
CLK low pulse width		tCL	2.5		2.5	
Input setup time		tSS	1.5		1.5	
Input hold time		tSH	1		0.8	
CLK to output in Low-Z		tSLZ	1		1	
CLK to output in Hi-Z	CAS latency=3	tSHZ		5		5.4
	CAS latency=2			-		6

NOTE : 1. Parameters depend on programmed CAS latency.

2. If clock rising time is longer than 1ns, (tr/2-0.5)ns should be added to the parameter.

3. Assumed input rise and fall time (tr & tf) = 1ns.

If tr & tf is longer than 1ns, transient time compensation should be considered, i.e., [(tr + tf)/2-1]ns should be added to the parameter.

4. tSS applies for address setup time, clock enable setup time, command setup time and data setup time.

tSH applies for address setup time, clock enable setup time, command setup time and data setup time.

16. DQ BUFFER OUTPUT DRIVE CHARACTERISTICS

Parameter	Symbol	Condition	Min	Typ	Max	Unit	NOTE
Output rise time	trh	Measure in linear region : 1.2V ~ 1.8V	1.37		4.37	Volts/ns	3
Output fall time	tfh	Measure in linear region : 1.2V ~ 1.8V	1.30		3.8	Volts/ns	3
Output rise time	trh	Measure in linear region : 1.2V ~ 1.8V	2.8	3.9	5.6	Volts/ns	1,2
Output fall time	tfh	Measure in linear region : 1.2V ~ 1.8V	2.0	2.9	5.0	Volts/ns	1,2

NOTE : 1. Rise time specification based on 0pF + 50 Ω to VSS, use these values to design to.

2. Fall time specification based on 0pF + 50 Ω to VDD, use these values to design to.

3. Measured into 50pF only, use these values to characterize to.

4. All measurements done with respect to VSS.

17. IBIS SPECIFICATION

[Table 2] IOH Characteristics (Pull-up)

Voltage	200MHz 166MHz 133MHz Min	200MHz 166MHz 133MHz Max
(V)	I (mA)	I (mA)
3.45		-2.4
3.3		-27.3
3.0	0.0	-74.1
2.6	-21.1	-129.2
2.4	-34.1	-153.3
2.0	-58.7	-197.0
1.8	-67.3	-226.2
1.65	-73.0	-248.0
1.5	-77.9	-269.7
1.4	-80.8	-284.3
1.0	-88.6	-344.5
0.0	-93.0	-502.4




Figure 4. 200MHz/166MHz/133MHz Pull-up

[Table 3] IOL Characteristics (Pull-down)

Voltage	200MHz 166MHz 133MHz Min	200MHz 166MHz 133MHz Max
(V)	I (mA)	I (mA)
0.0	0.0	0.0
0.4	27.5	70.2
0.65	41.8	107.5
0.85	51.6	133.8
1.0	58.0	151.2
1.4	70.7	187.7
1.5	72.9	194.4
1.65	75.4	202.5
1.8	77.0	208.6
1.95	77.6	212.0
3.0	80.3	219.6
3.45	81.4	222.6




Figure 5. 200MHz/166MHz/133MHz Pull-down

[Table 4] V_{DD} Clamp @ CLK, CKE, $\overline{CS}$, DQM & DQ

V_{DD} (V)	I (mA)
0.0	0.0
0.2	0.0
0.4	0.0
0.6	0.0
0.7	0.0
0.8	0.0
0.9	0.0
1.0	0.23
1.2	1.34
1.4	3.02
1.6	5.06
1.8	7.35
2.0	9.83
2.2	12.48
2.4	15.30
2.6	18.31




Figure 6. Minimum V_{DD} clamp current (Referenced to V_{DD})

[Table 5] V_{SS} Clamp @ CLK, CKE, $\overline{CS}$, DQM & DQ

V_{SS} (V)	I (mA)
-2.6	-57.23
-2.4	-45.77
-2.2	-38.26
-2.0	-31.22
-1.8	-24.58
-1.6	-18.37
-1.4	-12.56
-1.2	-7.57
-1.0	-3.37
-0.9	-1.75
-0.8	-0.58
-0.7	-0.05
-0.6	0.0
-0.4	0.0
-0.2	0.0
0.0	0.0




Figure 7. Minimum V_{SS} clamp current

18. SIMPLIFIED TRUTH TABLE

(V=Valid, X=Don't care, H=Logic high, L=Logic low)

Command			CKEn-1	CKEn	$\overline{CS}$	$\overline{RAS}$	$\overline{CAS}$	$\overline{WE}$	DQM	BA0,1	A10/AP	A0 ~ A9, A11,	NOTE
Register	Mode register set		H	X	L	L	L	L	X	OP code			1,2
Refresh	Auto refresh		H	H	L	L	L	H	X	X			3
	Self refresh	Entry		L									3
		Exit	L	H	L	H	H	H	X	X			3
					H	X	X	X					3
Bank active & row addr.			H	X	L	L	H	H	X	V	Row address		
Read & column address	Auto precharge disable		H	X	L	H	L	H	X	V	L	Column address	4
	Auto precharge enable										H		4,5
Write & column address	Auto precharge disable		H	X	L	H	L	L	X	V	L	Column address	4
	Auto precharge enable										H		4,5
Burst stop			H	X	L	H	H	L	X	X			6
Precharge	Bank selection		H	X	L	L	H	L	X	V	L	X	
	All banks									X	H		
Clock suspend or active power down		Entry	H	L	H	X	X	X	X	X			
					L	V	V	V					
Exit		L	H	X	X	X	X	X	X				
Precharge power down mode		Entry	H	L	H	X	X	X	X	X			
					L	H	H	H					
		Exit	L	H	H	X	X	X	X				
					L	V	V	V					
DQM			H	X					V	X			7
No operation command			H	X	H	X	X	X	X	X			
					L	H	H	H					

NOTE :

- OP Code : Operand code
A0 ~ A11 & BA0 ~ BA1 : Program keys. (@ MRS)
- MRS can be issued only at all banks precharge state.
A new command can be issued after 2 CLK cycles of MRS.
- Auto refresh functions are as same as CBR refresh of DRAM.
The automatical precharge without row precharge command is meant by "Auto".
Auto/self refresh can be issued only at all banks precharge state.
- BA0 ~ BA1 : Bank select addresses.
If both BA0 and BA1 are "Low" at read, write, row active and precharge, bank A is selected.
If BA0 is "High" and BA1 is "Low" at read, write, row active and precharge, bank B is selected.
If BA0 is "Low" and BA1 is "High" at read, write, row active and precharge, bank C is selected.
If both BA0 and BA1 are "High" at read, write, row active and precharge, bank D is selected.
If A10/AP is "High" at row precharge, BA0 and BA1 is ignored and all banks are selected.
- During burst read or write with auto precharge, new read/write command can not be issued.
Another bank read/write command can be issued after the end of burst.
New row active of the associated bank can be issued at tRP after the end of burst.
- Burst stop command is valid at every burst length.
- DQM sampled at positive going edge of a CLK and masks the data-in at the very CLK (Write DQM latency is 0), but makes Hi-Z state the data-out of 2 CLK cycles after. (Read DQM latency is 2)