




# TAN150

150 Watts, 50 Volts, Pulsed  
Avionics 960 - 1215 MHz

## GENERAL DESCRIPTION

The TAN150 is a high powered COMMON BASE bipolar transistor. It is designed for pulsed systems in the frequency band 960-1215 MHz. The device has gold thin-film metallization and diffused ballasting for proven highest MTTF. The transistor includes input and output prematch for broadband capability. Low thermal resistance package reduces junction temperature, extends life.

## CASE OUTLINE 55AT, Style 1



## ABSOLUTE MAXIMUM RATINGS

### Maximum Power Dissipation

Device Dissipation @25°C 583 W

### Maximum Voltage and Current

Collector to Base Voltage ( $BV_{ces}$ ) 55 V

Emitter to Base Voltage ( $BV_{ebo}$ ) 3.5 V

Collector Current ( $I_c$ ) 15.0 A

### Maximum Temperatures

Storage Temperature -65 to +150 °C

Operating Junction Temperature +200 °C

## ELECTRICAL CHARACTERISTICS @ 25°C

SYMBOL	CHARACTERISTICS	TEST CONDITIONS	MIN	TYP	MAX	UNITS
$P_{out}$	Power Out	F = 960-1215 MHz	150			W
$P_{in}$	Power Input	$V_{cc} = 50$ Volts			30	W
$P_g$	Power Gain	PW = 20 $\mu$ sec	7.0			dB
$\eta_c$	Collector Efficiency	DF = 5%		38		%
VSWR	Load Mismatch Tolerance	F = 1090 MHz			10:1	

## FUNCTIONAL CHARACTERISTICS @ 25°C

$BV_{ebo}$	Emitter to Base Breakdown	$I_e = 10$ mA	3.5			V
$BV_{ces}$	Collector to Emitter Breakdown	$I_c = 50$ mA	55			V
$h_{FE}$	DC - Current Gain	$V_{ce} = 5V, I_c = 1$ A	10			
$\theta_{jc}^1$	Thermal Resistance				0.3	°C/W


NOTE 1: At rated output power and pulse conditions

Rev A: Updated June 2009

MICROSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE. MICROSEMI RECOMMENDS THAT BEFORE THE PRODUCT(S) DESCRIBED HEREIN ARE WRITTEN INTO SPECIFICATIONS, OR USED IN CRITICAL APPLICATIONS, THAT THE PERFORMANCE CHARACTERISTICS BE VERIFIED BY CONTACTING THE FACTORY.

Microsemi: 3000 Oakmead Village Drive, Santa Clara, CA 95051-0808 Tel. 408 / 986-8031 Fax 408 / 986-8120


**TAN150 CASE DRAWING:**



DIM	MILLIMETER	±TOL	INCHES	±TOL
A	20.32	.76	.800	.050
B	10.16	.13	.400	.005
C	9.78	.13	.385	.005
D	45°	5°	45°	5°
E	3.81	.13	.150	.005
F	1.47	.25	.058	.010
G	1.52R	.13	.060R	.005
H	3.05	.25	.120	.010
I	3.25 DIA	.13	.128 DIA	.005
J	22.86	.13	.900	.005
K	16.51	.13	.650	.005
M	4.70	REF	.185	REF
N	0.10	.02	.004	.001

**STYLE 1:**  
**PIN 1 = COLLECTOR**  
**2 = BASE**  
**3 = EMITTER**

**STYLE 2:**  
**PIN 1 = COLLECTOR**  
**2 = EMITTER**  
**3 = BASE**




DWG NO.

**55AT**

MICROSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE. MICROSEMI RECOMMENDS THAT BEFORE THE PRODUCT(S) DESCRIBED HEREIN ARE WRITTEN INTO SPECIFICATIONS, OR USED IN CRITICAL APPLICATIONS, THAT THE PERFORMANCE CHARACTERISTICS BE VERIFIED BY CONTACTING THE FACTORY.

Microsemi: 3000 Oakmead Village Drive, Santa Clara, CA 95051-0808 Tel. 408 / 986-8031 Fax 408 / 986-8120

# TAN150 TEST CIRCUIT:



MICROSEMI. RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE. MICROSEMI RECOMMENDS THAT BEFORE THE PRODUCT(S) DESCRIBED HEREIN ARE WRITTEN INTO SPECIFICATIONS, OR USED IN CRITICAL APPLICATIONS, THAT THE PERFORMANCE CHARACTERISTICS BE VERIFIED BY CONTACTING THE FACTORY.

Microsemi: 3000 Oakmead Village Drive, Santa Clara, CA 95051-0808 Tel. 408 / 986-8031 Fax 408 / 986-8120