

**General Product and Reference Design Search**

[Go](#)

Please enter in a search term.

**VI Part Number: PX-7020-0064-16M0000000 - Frequency: 16.000000 MHz**



PX-702 High Temp XO Page

**Specifications:**  
Please contact Vectron for the custom datasheet

**Standard Features:**  
Output: HCMOS/ACMOS  
Frequencies: 32.7680 kHz to 40.0000 MHz  
Package: 5.0 x 7.0 x 1.8 SMD  
Power Supply: 1.8, 2.5, 3.3, 5.0 V  
Design for high shock & vibration  
Small footprint and low profile

**More Information:**  
[Standard Datasheet](#)  
[High Temperature Electronics](#)

**Other PX-702 High Temperature Crystal Oscillators to Consider**

[Expand \[+\]](#)

**You Might Also be Interested in These Products**

PX-420 High Temperature Crystal Oscillator



[Datasheet](#)

PX-570 High Temperature Crystal Oscillator



[Datasheet](#)

VX-400 High Temperature Voltage Controlled Crystal Oscillator



[Datasheet](#)

**Keyword Search Matrix Table**

ADEV	Clock & Data Recovery	Ethernet	GPS Disciplining	G-Sensitivity	High Stability
Hi-Rel TCXO	Hi-Rel OCXO	Holdover Oscillator	Jitter Cleaning	Low Jitter	Low Phase Noise
Low Aging	MEMS Oscillator	MTIE	1588	100G	OCXO Replacement
PEC Local Reference	Phase Accuracy	PLL	Rubidium Replacement	Ruggedized	Sensor Products
Shock & Vibration	Short Term Stability	Space OCXO	Stratum 3 & 3E	Synchronous Ethernet	TDD Mode
TDEV	High Temp (250°C)	Small Cell	Base Station		