

# PD-95xxGC Family

Multi-Port IEEE® 802.3bt-Compliant 60W PoE Midspan Family with Network Management



## Summary

Microchip's PD-95xxGC family is a 6-, 12- and 24-port solution for remote powering of current and emerging high-power applications. The PD-95xxGC family is designed specifically to power IEEE 802.11 access points, Pan-Tilt-Zoom (PTZ) and dome cameras, IP videophones, thin clients and other high-power Ethernet end terminals with 60W of power. This family supports IEEE 802.3bt-powered devices and is also backward compatible and safe to use with any IEEE 802.3af/at terminal. It can power both existing 10/100Base-T devices and Gigabit devices. With the midspan's plug-and-play installation, they are easy and cost effective to implement leveraging existing Ethernet infrastructure while at the same time providing the assurance of a future proof network.

## Product Features

- Supports IEEE802.3bt type 3 standard PDs
- IEEE 802.3af/at backward compatible
- Legacy and pre-standard support
- 6, 12 and 24 ports
- Supports 10/100/1000 Mbps,
- PowerView Pro, remote web-based SNMPv3 power management environment

Feature	Description
<b>Number of Ports</b>	6/12/24
<b>Data Rate</b>	10/100/1000 Mbps
<b>Input Power Requirement</b>	AC Input Voltage: 100 to 240 VAC AC Input Current: 6-port 450W unit - 5A @ 100 VAC 12-port 950W unit - 9A @ 100 VAC 24-port 950W unit - 12A @ 100 VAC AC Frequency: 50/60 Hz
<b>Output Power</b>	User Port Power: 60 Watts Aggregate Power: 450W (6-port), 950W (12-port) or 950W (24-port)
<b>Power over Ethernet Output</b>	Spare Pair: 4/5(+), 7/8(-) Data Pair: 3/6(+), 1/2(-) Nominal Output Voltage: 54 Vdc
<b>Dimensions</b>	L x W x H 438 mm x 272 mm x 44 mm 17.3 in. x 10.8 in. x 1.75 in.
<b>Net Weight</b>	PD-9506GC 4.54 kg PD-9512GC 5.34 kg PD-9524GC 5.48 kg
<b>Connectors</b>	Ports: 6-port Gang Shielded RJ-45, EIA 568A and 568B AC Connector: IEC 69320 type C14 DC Connector: Terminal Block Connector. two positive (+) and two negative. (-) terminals Communication Port: USB Type A and Shielded RJ45
<b>Indicators</b>	System Indicator: AC Power—Green User Indicator: Valid Load—Green (4 Pair) User Indicator: Valid Load—Yellow (2 Pair) User Indicator: Overload or Short circuit - Green blinks 0.5 Hz
<b>Management</b>	PowerView Pro included
<b>Environmental Conditions</b>	Operating Ambient Temperature: 32°F to 104°F (0°C to +40°C) Operating Humidity: 90% Maximum, Non-Condensing Storage Temperature: -4°F to +158°F (-20°C to +70°C) Storage Humidity: 95% Maximum, Non-Condensing Operating Altitude -1000 to 6,561ft (-304.8 to 2000m)
<b>Hazardous Substances</b>	CE, WEEE
<b>Warranty</b>	3 years
<b>Extended Warranty Available</b>	Contact Microchip
<b>Reliability</b>	MTBF: 100,000hrs
<b>Thermal Rating</b>	234 BTU/Hr (6 Port) 432 BTU/Hr (12 Port) 525 BTU/Hr (24 Port)
<b>Regulatory Compliance</b>	IEEE 802.3bt, IEEE802.3af/at
<b>Electromagnetic Emission and Immunity</b>	FCC Part 15, Class B EN 55032 Class B EN 55024 VCCI
<b>Safety</b>	UL/IEC/EN 62368-1

## Technical Support

For technical support, please visit the Microchip Technical Support Portal at [www.microchip.com/support](http://www.microchip.com/support).

## Management Software

PowerView Pro software is available on [Microchip's Software Library](#).

## Ordering Information

Part Number	Product Name	Description
<b>PD-9506GC/AC-xx</b> PD-9506GC/AC-AU: AU Power Cord PD-9506GC/AC-EU: EU Power Cord PD-9506GC/AC-JP: Japan Power Cord PD-9506GC/AC-UK: UK Power Cord PD-9506GC/AC-US: US Power Cord	PD-9506GC/AC	6-port BT midspan, 4-pairs 60W/port, managed, 10/100/1000 BaseT, AC input
<b>PD-9512GC/AC-xx</b> PD-9512GC/AC-AU: AU Power Cord PD-9512GC/AC-EU: EU Power Cord PD-9512GC/AC-JP: Japan Power Cord PD-9512GC/AC-UK: UK Power Cord PD-9512GC/AC-US: US Power Cord	PD-9512GC/AC	12-port BT midspan, 4-pairs 60W/port, managed, 10/100/1000 BaseT, AC input
<b>PD-9524GC/AC-xx</b> PD-9524GC/AC-AU: AU Power Cord PD-9524GC/AC-EU: EU Power Cord PD-9524GC/AC-JP: Japan Power Cord PD-9524GC/AC-UK: UK Power Cord PD-9524GC/AC-US: US Power Cord	PD-9524GC/AC	24-port BT midspan, 4-pairs 60W/port, managed, 10/100/1000 BaseT, AC input

Contact Microchip for other options

## About Microchip mPoE



Microchip multi-Power over Ethernet (mPoE) is a technology that powers any wired network device seamlessly and efficiently, making it the ideal solution for Ethernet-based applications. Leveraging a uniquely designed algorithm, this technology solves interoperability issues between different PoE standards and legacy solutions to provide an international network power standard. As a pioneer in PoE technology, we offer a comprehensive end-to-end portfolio of PoE solutions comprised of PoE ICs and PoE systems (midspans/injectors and switches).