



P-CHANNEL MOSFET
Qualified per MIL-PRF-19500/564

Qualified Levels:
 JAN, JANTX, JANTXV
 and JANS

DESCRIPTION

This 2N6849 switching transistor is military qualified up to the JANS level for high-reliability applications. This device is also available in a low profile U surface mount package. Microsemi also offers numerous other transistor products to meet higher and lower power ratings with various switching speed requirements in both through-hole and surface-mount packages.

Important: For the latest information, visit our website <http://www.microsemi.com>.

FEATURES

- JEDEC registered 2N6849 number.
- JAN, JANTX, JANTXV and JANS qualifications are available per MIL-PRF-19500/564. (See [part nomenclature](#) for all available options.)
- RoHS compliant versions available (commercial grade only).

APPLICATIONS / BENEFITS

- Lightweight top-hat design with flexible terminals offers a variety of mounting flexibility.
- Military and other high-reliability applications.


MAXIMUM RATINGS @ T_A = +25°C unless otherwise stated

Parameters / Test Conditions	Symbol	Value	Unit
Operating & Storage Junction Temperature Range	T _J & T _{stg}	-55 to +150	°C
Thermal Resistance Junction-to-Case	R _{θJC}	5.0	°C/W
Total Power Dissipation	P _T	@ T _A = +25 °C	0.8
		@ T _C = +25 °C ⁽¹⁾	25
Drain-Source Voltage, dc	V _{DS}	-100	V
Gate-Source Voltage, dc	V _{GS}	± 20	V
Drain Current, dc @ T _C = +25 °C ⁽²⁾	I _{D1}	-6.5	A
Drain Current, dc @ T _C = +100 °C ⁽²⁾	I _{D2}	-4.1	A
Off-State Current (Peak Total Value) ⁽³⁾	I _{DM}	-25	A (pk)
Source Current	I _S	-6.5	A

- Notes:**
1. Derate linearly 0.2 W/°C for T_C > +25 °C.
 2. The following formula derives the maximum theoretical I_D limit. I_D is also limited by package and internal wires and may be limited due to pin diameter.

$$I_D = \sqrt{\frac{T_J(\text{max}) - T_C}{R_{\theta JC} \times R_{DS(\text{on})} @ T_J(\text{max})}}$$

3. I_{DM} = 4 × I_{D1} as calculated in note 2.



**TO-205AF (TO-39)
 Package**

Also available in:

U-18 LCC package
 (surface mount)
 [2N6849U](#)

MSC – Lawrence

6 Lake Street,
 Lawrence, MA 01841
 Tel: 1-800-446-1158 or
 (978) 620-2600
 Fax: (978) 689-0803

MSC – Ireland


Gort Road Business Park,
 Ennis, Co. Clare, Ireland
 Tel: +353 (0) 65 6840044
 Fax: +353 (0) 65 6822298

Website:

www.microsemi.com

MECHANICAL and PACKAGING

- CASE: Hermetically sealed, kovar base, nickel cap.
- TERMINALS: Tin/lead solder dip nickel plate or RoHS compliant pure tin plate (commercial grade only).
- MARKING: Part number, date code, manufacturer's ID.
- WEIGHT: Approximately 1.064 grams.
- See [Package Dimensions](#) on last page.

PART NOMENCLATURE

SYMBOLS & DEFINITIONS

Symbol	Definition
di/dt	Rate of change of diode current while in reverse-recovery mode, recorded as maximum value.
I _F	Forward current
R _G	Gate drive impedance
V _{DD}	Drain supply voltage
V _{DS}	Drain source voltage, dc
V _{GS}	Gate source voltage, dc

ELECTRICAL CHARACTERISTICS @ $T_A = +25\text{ }^\circ\text{C}$, unless otherwise noted

Parameters / Test Conditions	Symbol	Min.	Max.	Unit
OFF CHARACTERISTICS				
Drain-Source Breakdown Voltage $V_{GS} = 0\text{ V}$, $I_D = -1.0\text{ mA}$	$V_{(BR)DSS}$	-100		V
Gate-Source Voltage (Threshold) $V_{DS} \geq V_{GS}$, $I_D = -0.25\text{ mA}$ $V_{DS} \geq V_{GS}$, $I_D = -0.25\text{ mA}$, $T_J = +125\text{ }^\circ\text{C}$ $V_{DS} \geq V_{GS}$, $I_D = -0.25\text{ mA}$, $T_J = -55\text{ }^\circ\text{C}$	$V_{GS(th)1}$ $V_{GS(th)2}$ $V_{GS(th)3}$	-2.0 -1.0	-4.0 -5.0	V
Gate Current $V_{GS} = \pm 20\text{ V}$, $V_{DS} = 0\text{ V}$ $V_{GS} = \pm 20\text{ V}$, $V_{DS} = 0\text{ V}$, $T_J = +125\text{ }^\circ\text{C}$	I_{GSS1} I_{GSS2}		± 100 ± 200	nA
Drain Current $V_{GS} = 0\text{ V}$, $V_{DS} = -80\text{ V}$	I_{DSS1}		-25	μA
Drain Current $V_{GS} = 0\text{ V}$, $V_{DS} = -80\text{ V}$, $T_J = +125\text{ }^\circ\text{C}$	I_{DSS2}		-0.25	mA
Static Drain-Source On-State Resistance $V_{GS} = -10\text{ V}$, $I_D = -4.1\text{ A}$ pulsed	$r_{DS(on)1}$		0.30	Ω
Static Drain-Source On-State Resistance $V_{GS} = -10\text{ V}$, $I_D = -6.5\text{ A}$ pulsed	$r_{DS(on)2}$		0.32	Ω
Static Drain-Source On-State Resistance $T_J = +125\text{ }^\circ\text{C}$ $V_{GS} = -10\text{ V}$, $I_D = -4.1\text{ A}$ pulsed	$r_{DS(on)3}$		0.54	Ω
Diode Forward Voltage $V_{GS} = 0\text{ V}$, $I_D = -6.5\text{ A}$ pulsed	V_{SD}		-4.3	V

DYNAMIC CHARACTERISTICS

Parameters / Test Conditions	Symbol	Min.	Max.	Unit
Gate Charge:				
On-State Gate Charge $V_{GS} = -10\text{ V}$, $I_D = -6.5\text{ A}$, $V_{DS} = -50\text{ V}$	$Q_{g(on)}$		34.8	nC
Gate to Source Charge $V_{GS} = -10\text{ V}$, $I_D = -6.5\text{ A}$, $V_{DS} = -50\text{ V}$	Q_{gs}		6.8	nC
Gate to Drain Charge $V_{GS} = -10\text{ V}$, $I_D = -6.5\text{ A}$, $V_{DS} = -50\text{ V}$	Q_{gd}		23.1	nC

ELECTRICAL CHARACTERISTICS @ $T_A = +25\text{ }^\circ\text{C}$, unless otherwise noted (continued)**SWITCHING CHARACTERISTICS**

Parameters / Test Conditions	Symbol	Min.	Max.	Unit
Turn-on delay time $I_D = -6.5\text{ A}$, $V_{GS} = -10\text{ V}$, $R_G = 7.5\ \Omega$, $V_{DD} = -40\text{ V}$	$t_{d(\text{on})}$		60	ns
Rinse time $I_D = -6.5\text{ A}$, $V_{GS} = -10\text{ V}$, $R_G = 7.5\ \Omega$, $V_{DD} = -40\text{ V}$	t_r		140	ns
Turn-off delay time $I_D = -6.5\text{ A}$, $V_{GS} = -10\text{ V}$, $R_G = 7.5\ \Omega$, $V_{DD} = -40\text{ V}$	$t_{d(\text{off})}$		140	ns
Fall time $I_D = -6.5\text{ A}$, $V_{GS} = -10\text{ V}$, $R_G = 7.5\ \Omega$, $V_{DD} = -40\text{ V}$	t_f		140	ns
Diode Reverse Recovery Time $di/dt \leq -100\text{ A}/\mu\text{s}$, $V_{DD} \leq -50\text{ V}$, $I_F = -6.5\text{ A}$	t_{rr}		250	ns

GRAPHS




FIGURE 1 – Normalized Transient Thermal Impedance




FIGURE 2 – Maximum Drain Current vs Case Temperature

GRAPHS (continued)







FIGURE 3 – Maximum Safe Operating Area

PACKAGE DIMENSIONS


Symbol	Dimensions				Note
	Inch		Millimeters		
	Min	Max	Min	Max	
CD	0.305	0.335	7.75	8.51	
CH	0.160	0.180	4.07	4.57	
HD	0.335	0.370	8.51	9.39	
LC	0.200 TP		5.08 TP		6
LD	0.016	0.021	0.41	0.53	7, 8
LL	0.500	0.750	12.70	19.05	7, 8
LU	0.016	0.019	0.41	0.48	7, 8
L1	-	0.050	-	1.27	7, 8
L2	0.250	-	6.35	-	7, 8
P	0.100	-	2.54	-	5
Q	-	0.050	-	1.27	4
TL	0.029	0.045	0.74	1.14	3
TW	0.028	0.034	0.72	0.86	2
r	-	0.010	-	0.25	9
α	45° TP		45° TP		6


Schematic
NOTES:

- Dimensions are in inches. Millimeters are given for general information only.
- Beyond radius (r) maximum, TW shall be held for a minimum length of 0.011 (0.028 mm).
- Dimension TL measured from maximum HD.
- Outline in this zone is not controlled.
- Dimension CD shall not vary more than 0.010 (0.25 mm) in zone P. This zone is controlled for automatic handling.
- Leads at gauge plane 0.054 +0.001, -0.000 (1.37 +0.03, -0.00 mm) below seating plane shall be within 0.007 (0.18 mm) radius of true position (TP) at maximum material condition (MMC) relative to tab at MMC.
- LU applies between L1 and L2. LD applies between L2 and LL minimum. Diameter is uncontrolled in L1 and beyond LL minimum.
- All three leads.
- Radius (r) applies to both inside corners of tab.
- Drain is electrically connected to the case.
- In accordance with ASME Y14.5M, diameters are equivalent to Φ x symbology.
- Lead 1 = source, lead 2 = gate, lead 3 = drain.